imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



NOTE:			242 38 REVISIONS DRAWING NO. REV DESCRIPTION DATE ECO AF		
1. ELECTRIC PERFORMANCE		DRAWING NO. THIRD ANGLE PROJ. 🔶	REV DESCRI → ← NC INITIAL		ECO APPR
IMPEDANCE (Ω) : 50		THIRD ANGLE FROJ.	A UPDATED DRAV		
FREQUENCY RANGE : DC-6GHz VSWR : ≤ 1.065 (DC-3GHz)			B UPDATED DRAWING AS		 2116 CL
: ≤1.2 (3-6GHz)					2116 CL
INSERT LOSS (dB) : ≤ 0.1 PIM(dBc) : ≤-160 (2X43dBm)			C LOW PIM ADDED & ISOMETRIC	VIEW ADDED 01-Oct-12 2	2387 KR
INSULATION RESISTANCE (M Ω) : >5000					I
PROOF VOLTAGE (V) :2500					
CONDUCTOR RESISTANCE (m Ω) : OUTER CONDUCTOR <0.2 INNER CONDUCTOR <0.8	-				
		[].90]			N (
II. MECHANICAL PERFORMANCE NUT TORQUE 7/16 : 25N.m N : 5N.m					
MECHANICAL WEAR : 500		ו			
III. MATERIAL AND PLATING					per
INNER CONDUCTOR : SPRING COPPER PLATING Ag5 µm					
OUTER CONDUCTOR : BRASS PLATING COPPER-TIN-ZINC 2 µm					4
NUT : BRASS PLATING Ni5µm INSULATOR : PTFE				SCALE	1.000
			$\boldsymbol{\lambda}$		
IV. ENVIRONMENT TEMP RANGE : -55 °C TO +155 °C			Ŋ		
WATERPROOF STANDARD : IP67					
ROHS COMPLIANT					
		╫╶──╶──╟╢┼┼╟┼─╶──╶──╴			
			/		
		J			
4 INSULATOR PTFE NATURAL 1					
3 NUT BRASS NICKEL 1	1.260 ON HEX-		0.748 ON HEX		
2 OUTER CONDUCTOR BRASS WHITE BRONZE 1	[32.00]		[19.00]		
1 INNER CONDUCTOR SPRING COPPER SILVER 1					
NO DESCRIPTION MATERIAL FINISH QTY		2.2.1.11			
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES	MATERIAL		ράτε τιτιε)1-0ct-12 7/14 ΜΛΙΓΤ		
±.015 (0,381 mm) ±.005 (0,127 mm) ± 1°	SEE NOTES		//IU HALL I		nol
NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are			ADAPTER, LC	IWPIM Conne	e x
confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or	REFERENCE		DATE		~ / `
other data by Amphenol Corp., or to any other person to anyone for any purpose is				SCALE: 4.4:1 SHEET	
not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any		CAD FILE		OWG SIZE DRAWING NO.	REV
product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.				B 242138	
or anochosca by sura arawnings, specifications, or office auta.					



TO N MALE Ow PIM		oheno onnex	
	SCALE: 4.4:1	SHEET I	OF I
DWG SIZE DRAWING NC	5. 42138		r e v C