imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



NOTES:	242280	REVISIONS	
REFERENCE STANDARD IEC60169-11 (4.1/9.5) IEC60169-16 (N)	DRAWING NO. RE		DATE ECO APPR
I. ELECTRICAL PERFORMANCE -	THIRD ANGLE PROJ. 🕀 🗧 A	RELEASE TO MFG.	II-Sep-I3 AAP/BG
NOMINAL IMPEDANCE: 50 Ω FREQUENCY RANGE: DC-3.0 GHzVSWR: 1.065 MAXPIM: -160 dBc MAX.(1800 MHz)INSERTION LOSS: 0.05 dB MAX.INSULATION RESISTANCE: 5000 M Ω MIN.PROOF VOLTAGE: 2500 VRMSCONDUCTOR RESISTANCE: OUTER CONDUCTOR 0.4 m Ω MAX. (N), 0.5 m Ω (4.1/9.5)INNER CONDUCTOR 0.8 m Ω MAX. (N), 1.0 m Ω (4.1/9.5)			
II. MECHANICAL PERFORMANCE -			SCALE I.000
RETENTION : 0.56N MIN.(N), 4.0N MIN.(4.1/9.5) MATING CYCLES : 500 MIN.			
III. MATERIAL AND PLATING-			
INNER CONDUCTOR : SPRING BRONZE ALLOY, PLATING = Ag (5µm MIN.) OUTER CONDUCTOR : BRASS, PLATING = Ag (5µm MIN.) NUT : BRASS, PLATING = NI (5µm) INSULATOR : PTFE	——————————————————————————————————————		
IV. ENVIRONMENTAL -			
TEMP. RANGE : -40°C TO +85°C WEATHER STANDARD : IEC 60068 40/ 85/ 21 THERMAL SHOCK : IEC 60068-2-16-FC SHOCK : IEC 60068-2-27 V. ROHS COMPLIANT V. ROHS COMPLIANT 4.1/9.5 FEMALE INTERFACE M20x1 0.669 ON [17.0]	FLATS	-0.551 ON FLATS E14.0]	
		ALL OTHER SHEETS ARE	FOR INTERNAL USE ONLY
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES ±.015 (0,381 mm) ±.005 (0,127 mm) ± 1° SEE NOTES	DRAWN DATE A ARUN PRABU 05-Sep-13	4.1/9.5 FEMALE TO N	Amphenol
NOTICE - These drawings, specifications, or other data (I) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are	ENGINEER DATE	EEMALE ADADTED	Connex
confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is	APPROVED DATE	—	
not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any	B.C. GLEISSNER II-Sep-13 CAD FILE	DWG SIZE DRAWING N	
product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.		В 2	42280 A