



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com



Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



This drawing is the property of Tusonix, Inc., and may not be used, reproduced, published or disclosed to others without expressed authorization by Tusonix Inc.

**Electrical Testing**  
per Tusonix standard  
test plans and Mil-Std-202  
Test Methods.

**MARKETING SALES DRAWING**  
**DIMENSIONS IN INCHES - DO NOT SCALE THIS DRAWING**  
**DIMENSIONS IN METRIC - [ ]**



**NOTES:**

- SUPPLIED WITH SILVER PLATED HEX NUT.
- MOUNTING TORQUE NOT TO EXCEED 5 lb-in. [.565 Nm].
- TUSONIX STANDARD PART NUMBER: 2425-001-X5U0-101AA. TUSONIX RoHS COMPLIANT PART NUMBER: 2425-001-X5U0-101AA LF. CUSTOMER MUST SPECIFY STANDARD OR RoHS PART NUMBER WHEN ORDERING.
- PART MARKING: STANDARD PART: BLACK INK FOR TRADEMARK AND CAP. CODE. RoHS PART: GREEN INK FOR TRADEMARK AND CAP. CODE.

\* GMV - GUARANTEED MINIMUM VALUE.

**SPECIFICATIONS**

Tusonix Style:	2425-001
Capacitance Value:	100 pF
Capacitance Tol.:	GMV *
Temp. Characteristic:	X5U
Rating:	200 VDC @ 85°C/100 @ 125°C
Operating Range:	-55°C TO +125°C
I.R. min. @ 100 (VDC.)	10 G Ω
DWV (VDC)	600

<b>REVISION RECORD</b>	Original Release	0
	C.O. 19991201-3-01	1
	RESCALE DRAWING. ADDED METRIC, IR, DWV & STYLE. REVISED TITLE; DIM .267 & .631. S.M. 01-04-05	2
	20050103-5-01	2
REVISED RATING, OPERATING RANGE & ADDED & REVISED NOTES. S.M. 03-08-06		
20060217-2-05		

--TOLERANCES-- Unless Otherwise Specified		Title <b>MINIATURE BUSHING FEED-THRU CAPACITOR</b>	
DECIMAL ± .031 [0.79]		Drawn S.M. 12-02-99	Scale 4 X
ANGLES ±		Approved T.C. 12-02-99	
 TUCSON, ARIZONA		A 2425-001-X5U0-101AA	