



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Daflon Microminiature PTFE Hook-Up Wire

Daflon Microminiature PTFE hook-up wire is chemically inert, weather resistant and non-flammable; it resists soldering irons and moisture; maintaining the benefits of PTFE wires, while in a tiny package. The Daflon microminiature series of ultra thin walled PTFE insulation offers savings of space and weight for applications ranging from medical, aircraft, missile, space and compact electronic components.

Description: Single conductor stranded silver plated copper covered with multiple layers of PTFE insulation. This construction allows for a uniform, flexible, concentric, quality construction.

Operating Temperature: -90°C to +250°C

Voltage Rating: 300V.

This series is RoHS compliant.

DAFLON Cat. No.	AWG	Strand	Nom. Wall		Nom. O.D.	
			IN.	MM	IN.	MM
2451/38	38	7/46	.0019	0.048	.0089	0.218
2451/36	36	7/44	.0020	0.051	.0101	0.257
2451/34	34	7/42	.0027	0.069	.0129	0.328
2451/32	32	7/40	.0030	0.076	.0153	0.389
2451/30	30	7/38	.0034	0.086	.0188	0.478

Standard Put-Ups: 500 FT, 1,000 FT.

Stock Colors: Black, Red, Green, White

Additional colors are available to order.

Additional Stranding (including solid conductors) are available.

Note: Above items can be laminated into a flat ribbon cable and twisted into multi-conductor cables.