## imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



NOTES:			245130-01-XX	XX	
1. MATERIALS AND FINISHES:			DRAWING NO.	REV	DESCR
SMA BULKHEAD CRIMP JACK - P/N: 132119 MCX RIGHT ANGLE CRIMP PLUG - P/N: 252102 CABLE - RG-316 CABLE			THIRD ANGLE PROJ.	⊕	RELEASE
2. ELECTRICAL:					
A. IMPEDANCE: 50 OHM. NOMINAL					
3. PACKAGING:					
A. QUANTITY: SINGLE PACK B. BAG TO BE MARKED: AMPHENOL RF, 245130-01-XX.XX, AND DATE CODE					
			EDANCE (SEE TADIE)		
		LENGTH AND TO	ERANCE (SEE TABLE) ———		
MCX RIGHT ANGLE CRIMP PLUG					
		55			
	<b>X</b>				
		RG 316 CABLE			heat shrink tube ——/
		RU JIO CADLL			TYP. (2x)
			H AND TOLERANCE		
		PART NUMBER	IN INCHES $6.00 \pm 0.25$		
			$2.00 \pm 0.25$		
			$8.00 \pm 0.25$ $4.00 \pm 0.25$		
			$\frac{4.00 \pm 0.25}{6.00 \pm 0.50}$		
		* ADDITIONAL LENGTHS C/ CONTACT AMPHENOL RF MA			
DESIGN REQUIREMENTS:		CONTACT ANTHENOL IN THA			
X FREQUENCY : DC TO 6 GHZ X CONTINUIT	ΤΥ				
VSWR : MAX X HI-POT :	500 VRMS				
INS. LOSS : dBMAX OTHER					
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES	MATERIAL	DRA	vn GOPAL N	DATE 24-Sep-14	TITLE
$\pm$ .015 (0,381 mm) $\pm$ .005 (0,127 mm) $\pm$ 1° NOTICE - These drawings, specifications, or other data (1) are, and remain the	SEE NOTES	ENG	INEER	DATE	MCX RIGHT ANGLE TO SMA BULKHEAD
property of Amphenol Ĉorp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they	REFERENCE		GOPAL N Roved	24-Sep-14	USING RG 316 CAB
are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting	EAR # 6452		GLEISSNER	DATE 28-Sep-14	VAROIUS LENGTHS
rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to		CAD	FILE		
or disclosed by said drawings, specifications, or other data.					

