



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China






Phase Control SCR TO-220AB FULL-PAK, 25 A



TO-220AB FULL-PAK



DESCRIPTION/FEATURES

The 25TTS...FP High Voltage Series of silicon controlled rectifiers are specifically designed for medium power switching and phase control applications. The glass passivation technology used has reliable operation up to 125 °C junction temperature.

Typical applications are in input rectification (soft start) and these products are designed to be used with Vishay HPP input diodes, switches and output rectifiers which are available in identical package outlines.

The fully isolated package ($V_{INS} = 2500 V_{RMS}$) is UL E78996 approved. Plastic material 94V_{RO}.

This product has been designed and qualified for industrial level.

| PRODUCT SUMMARY | |
|-----------------|------------|
| V_T at 16 A | < 1.25 V |
| I_{TSM} | 300 A |
| V_{RRM} | 800/1200 V |

| OUTPUT CURRENT IN TYPICAL APPLICATIONS | | | |
|--|---------------------|--------------------|-------|
| APPLICATIONS | SINGLE-PHASE BRIDGE | THREE-PHASE BRIDGE | UNITS |
| Capacitive input filter $T_A = 55\text{ °C}$, $T_J = 125\text{ °C}$, common heatsink of 1 °C/W | 18 | 22 | A |

| MAJOR RATINGS AND CHARACTERISTICS | | | |
|-----------------------------------|----------------------------|-------------|------------|
| PARAMETER | TEST CONDITIONS | VALUES | UNITS |
| $I_{T(AV)}$ | Sinusoidal waveform | 16 | A |
| I_{RMS} | | 25 | |
| V_{RRM}/V_{DRM} | | 800/1200 | V |
| I_{TSM} | | 300 | A |
| V_T | 16 A, $T_J = 25\text{ °C}$ | 1.25 | V |
| dV/dt | | 500 | V/ μ s |
| dI/dt | | 150 | A/ μ s |
| T_J | | - 40 to 125 | °C |

| VOLTAGE RATINGS | | | |
|-----------------|---|--|--------------------------------------|
| PART NUMBER | V_{RRM} , MAXIMUM PEAK REVERSE VOLTAGE V | V_{DRM} , MAXIMUM PEAK DIRECT VOLTAGE V | I_{RRM}/I_{DRM} AT 125 °C mA |
| 25TTS08FP | 800 | 800 | 10 |
| 25TTS12FP | 1200 | 1200 | |

25TTS...FP High Voltage Series



Vishay High Power Products Phase Control SCR
TO-220AB FULL-PAK, 25 A

| ABSOLUTE MAXIMUM RATINGS | | | | | | |
|---|-----------------|---|-----------------------------------|------|-------------------|----|
| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | | UNITS | |
| | | | TYP. | MAX. | | |
| Maximum average on-state current | $I_{T(AV)}$ | $T_C = 85\text{ }^\circ\text{C}$, 180° conduction half sine wave | 16 | | A | |
| Maximum RMS on-state current | I_{RMS} | | 25 | | | |
| Maximum peak, one-cycle, non-repetitive surge current | I_{TSM} | 10 ms sine pulse, rated V_{RRM} applied | 300 | | | |
| | | 10 ms sine pulse, no voltage reapplied | 350 | | | |
| Maximum I^2t for fusing | I^2t | 10 ms sine pulse, rated V_{RRM} applied | 450 | | A ² s | |
| | | 10 ms sine pulse, no voltage reapplied | 630 | | | |
| Maximum $I^2\sqrt{t}$ for fusing | $I^2\sqrt{t}$ | $t = 0.1$ to 10 ms, no voltage reapplied | 6300 | | A ² √s | |
| Maximum on-state voltage drop | V_{TM} | 16 A, $T_J = 25\text{ }^\circ\text{C}$ | 1.25 | | V | |
| On-state slope resistance | r_t | $T_J = 125\text{ }^\circ\text{C}$ | 12.0 | | mΩ | |
| Threshold voltage | $V_{T(TO)}$ | | 1.0 | | V | |
| Maximum reverse and direct leakage current | I_{RM}/I_{DM} | $V_R = \text{Rated } V_{RRM}/V_{DRM}$ | $T_J = 25\text{ }^\circ\text{C}$ | 0.5 | | mA |
| | | | $T_J = 125\text{ }^\circ\text{C}$ | 10 | | |
| Holding current | I_H | Anode supply = 6 V, resistive load, initial $I_T = 1$ A | - | 100 | | |
| Maximum latching current | I_L | Anode supply = 6 V, resistive load | 200 | | | |
| Maximum rate of rise of off-state voltage | dV/dt | | 500 | | V/μs | |
| Maximum rate of rise of turned-on current | dI/dt | | 150 | | A/μs | |

| TRIGGERING | | | | | |
|---|-------------|---|--------|-------|----|
| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | UNITS | |
| Maximum peak gate power | P_{GM} | | 8.0 | W | |
| Maximum average gate power | $P_{G(AV)}$ | | 2.0 | | |
| Maximum peak positive gate current | + I_{GM} | | 1.5 | A | |
| Maximum peak negative gate voltage | - V_{GM} | | 10 | V | |
| Maximum required DC gate current to trigger | I_{GT} | Anode supply = 6 V, resistive load, $T_J = -10\text{ }^\circ\text{C}$ | 60 | | mA |
| | | Anode supply = 6 V, resistive load, $T_J = 25\text{ }^\circ\text{C}$ | 45 | | |
| | | Anode supply = 6 V, resistive load, $T_J = 125\text{ }^\circ\text{C}$ | 20 | | |
| Maximum required DC gate voltage to trigger | V_{GT} | Anode supply = 6 V, resistive load, $T_J = -10\text{ }^\circ\text{C}$ | 2.5 | | V |
| | | Anode supply = 6 V, resistive load, $T_J = 25\text{ }^\circ\text{C}$ | 2.0 | | |
| | | Anode supply = 6 V, resistive load, $T_J = 125\text{ }^\circ\text{C}$ | 1.0 | | |
| Maximum DC gate voltage not to trigger | V_{GD} | $T_J = 125\text{ }^\circ\text{C}$, $V_{DRM} = \text{Rated value}$ | 0.25 | | |
| Maximum DC gate current not to trigger | I_{GD} | | 2.0 | | mA |

| SWITCHING | | | | | |
|-------------------------------|----------|-----------------------------------|--------|-------|----|
| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | UNITS | |
| Typical turn-on time | t_{gt} | $T_J = 25\text{ }^\circ\text{C}$ | 0.9 | | μs |
| Typical reverse recovery time | t_{rr} | $T_J = 125\text{ }^\circ\text{C}$ | 4 | | |
| Typical turn-off time | t_q | | 110 | | |



25TTS...FP High Voltage Series

Phase Control SCR Vishay High Power Products
TO-220AB FULL-PAK, 25 A

| THERMAL AND MECHANICAL SPECIFICATIONS | | | | |
|---|----------------|--------------------------------------|-------------|------------------------|
| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | UNITS |
| Maximum junction and storage temperature range | T_J, T_{Stg} | | - 40 to 125 | °C |
| Maximum thermal resistance, junction to case | R_{thJC} | DC operation | 1.5 | °C/W |
| Maximum thermal resistance, junction to ambient | R_{thJA} | | 62 | |
| Typical thermal resistance, case to heatsink | R_{thCS} | Mounting surface, smooth and greased | 1.5 | |
| Approximate weight | | | 2 | g |
| | | | 0.07 | oz. |
| Mounting torque | minimum | | 6 (5) | kgf · cm (lbf · in) |
| | maximum | | 12 (10) | |
| Marking device | | Case style TO-220AB FULL-PAK (94/V0) | 25TTS08FP | |
| | | | 25TTS12FP | |

25TTS...FP High Voltage Series



Vishay High Power Products

Phase Control SCR
TO-220AB FULL-PAK, 25 A




Fig. 1 - Current Rating Characteristics




Fig. 4 - On-State Power Loss Characteristics




Fig. 2 - Current Rating Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 3 - On-State Power Loss Characteristics




Fig. 6 - Maximum Non-Repetitive Surge Current



25TTS...FP High Voltage Series

Phase Control SCR Vishay High Power Products
TO-220AB FULL-PAK, 25 A




Fig. 7 - On-State Voltage Drop Characteristics




Fig. 8 - Thermal Impedance Z_{thJC} Characteristics





Fig. 9 - Gate Characteristics

25TTS...FP High Voltage Series



Vishay High Power Products Phase Control SCR
TO-220AB FULL-PAK, 25 A

ORDERING INFORMATION TABLE



- 1** - Current rating (25 = 25 A)
- 2** - Circuit configuration:
T = Single thyristor
- 3** - Package:
T = TO-220AB
- 4** - Type of silicon:
Standard recovery rectifier
- 5** - Voltage code x 100 = V_{RRM}

| |
|-------------|
| 08 = 800 V |
| 12 = 1200 V |
- 6** - FULL-PAK
- 7**
 - None = Standard production
 - PbF = Lead (Pb)-free

| LINKS TO RELATED DOCUMENTS | |
|----------------------------|---|
| Dimensions | http://www.vishay.com/doc?95072 |
| Part marking information | http://www.vishay.com/doc?95069 |



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.