

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Turn Counting Dial

Model 2600 Series



Features:

- 7/8" diameter
- Analog



| MODEL | | 2606 | 2607 | 2601 |
|------------------------------------|-----------------------------|--------------------------------|------|-----------------|
| Counting Capacity, Maximum Turns | | 20 | | 15 |
| For Shaft Diameter | | 1/4" | | 1/8" |
| For Bushing Diameter | | 3/8" | | 1/4" |
| Depth: Maximum, From Face of Panel | | 0.900" | | 0.82" |
| Shaft Extension: | Maximum, From Face of Panel | 0.781 | | 0.672" |
| | Minimum, From Face of Panel | 0.628" | | 0.469" |
| Bushing Extension: | Maximum, From Face of Panel | 0.300" | | 0.270" |
| Locking Mechanism | | Positive Action with Detent | | Positive Action |
| Weight, Nominal | | 0.60 oz. | | |
| Number of Set Screws | | 1 | 2 | 1 |
| Numeral Height | | 0.050" | | |
| Knob Material | | Black Plastic | | |
| Dial Finish | | Black Numerals on Satin Chrome | | |
| Housing Finish | | Satin Chrome | | |
| Operating Temperature Range | | -55°C to +71°C | | |

| 26065 | 26075 | |
|--------------------------------|--------------------------------------------------------------------------------------------------|--|
| 15 | | |
| 1/4" | | |
| 3/8" | | |
| 0.94" | | |
| 0.781" | | |
| 0.57 | 78" | |
| 0.300" | | |
| Positive Action | | |
| 0.60 oz. | | |
| 1 | 2 | |
| 0.050" | | |
| Black Plastic | | |
| Black Numerals on Satin Chrome | | |
| Satin Chrome | | |
| −55°C to +71°C | | |
| | 15 1/4 3/8 0.9 0.78 0.57 0.30 Positive 0.60 1 1 0.05 Black F | |

Model 2600 Series



