imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







larger image

Lumenera's INFINITY2-1 1.4 megapixel CCD digital camera is a versatile solution for clinical, life science, materials science, and educational professionals working under low light conditions. With 1392x1040 resolution and on-board processing, the INFINITY2-1 delivers outstanding image quality for a wide variety of scientific applications. Live video preview provides for real-time focus. INFINITY2-1 auto exposure and auto white balance controls efficiently captures your optimal image. The INFINITY2-1 is fully supported by Lumenera's INFINITY CAPTURE and INFINITY ANALYZE software. An intuitive user application provides camera controls while full integration to popular third-party imaging applications is available through our TWAIN drivers. The USB 2.0 digital interface ensures a simple plug-and-play installation - and one standard cable minimizes camera clutter. No framegrabber required. INFINITY2-1 is supported by an experienced team of

technical support and imaging experts. We understand your imaging needs and are here to help you get the most out of your camera.

CAMERA SENSOR

Image Sensor1/2" Interline Sony ICX205 1.4 megapixel color or monochrome progressive scanCCD sensor 7.6mm x 6.2mm arrayEffective Pixels1392 x 1040, 4.65μm square pixelsFrame Rate15 fps at 1392 x 1040, >200 fps with binning and ROIDynamic Range>66dBDigital Output8 and 12-bitRead Noise12 e- rmsReadout Frequency28.6 MHZDimensions2.25 x 3.85 x 1.56 inches (enclosed)

CAMERA CONTROLS

Integration Time 1/1000 to 16 sec. Shutter Global Shutter ROI User Selectable Auto Exposure Automatic / Manual White Balance Automatic / Manual Gain Programmable / 1 to 10x optimizable Interface Connector Standard USB 2.0 high-speed interface Dimensions (L x W x H) 3.85 x 2.00 x 2.75 inches Lens Mount C-Mount lens adapter Binning Options 2x2, 3x3, 4x4 Mass 300 g Power Requirement USB 2.0 bus power, or external 5VDC - 500 mA Power Consumption ~2.5Watts Operating Temperature 0° C to + 50° C Operating Humidity 5%-95%, Non-condensing

Downloadable Documents



Model: 26100-220 Shipping Weight: 1.5lbs

bbA	to	Cart:	1
AUU.	ιυ	Jan.	· ·

Add to Cart

Copyright © 2008 Aven, Inc. 4595 Platt Road Ann Arbor, MI 48104 734-973-0099 st