imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







larger image

Lumenera's INFINITY2-3 digital CCD color camera offers excellent sensitivity and high resolution. This is an ideal camera for brightfield, darkfield, and DIC imaging applications where higher resolution archiving and a wide dynamic range are routinely required. With 2080 x 1536 resolution and on-board processing, the INFINITY2-3 delivers outstanding image quality for a wide variety of scientific applications.

Live video preview provides for real-time focus while auto exposure and auto white balance efficiently captures your optimal image. The INFINITY2-3 is fully supported by Lumenera's INFINITY CAPTURE and INFINITY ANALYZE software. An intuitive user application provides camera controls while full integration to popular third-party imaging applications is available through our TWAIN drivers. The USB 2.0 digital interface ensures a simple

plug-and-play installation – and one standard cable minimizes camera clutter. No framegrabber required. The INFINITY2-3 camera is supported by an experienced team of technical support and imaging experts. We understand your imaging needs and are here to help you get the most out of your camera.

CAMERA SENSOR

Image Sensor1/1.8" Interline Sony ICX262 3.3 megapixel color progressive scan CCD sensorEffective Pixels2080 x 1536, 3.45μm square pixelsFrame Rate5 fps at full resolution, higher fps with binning and ROIDigital Output8 and 12-bitRead Noise12 e- rmsReadout Frequency22.5 MHZDimensions2.25 x 3.85 x 1.56 inches (enclosed)

CAMERA CONTROLS

Integration Time 1/1000 to 16 sec. Shutter Interlaced ROI User Selectable through mouse click and drag Auto Exposure Automatic / Manual White Balance Automatic / Manual Gain Programmable / 1 to 10x optimizable Interface Connector Standard USB 2.0 high-speed interface Dimensions (L x W x H) 3.85 x 2.00 x 2.75 inches Lens Mount C-Mount lens adapter Binning Options 2x2, 3x3, 4x4 Mass ~ 300 g Power Requirement USB 2.0 bus power, or external 5VDC - 500 mA Power Consumption ~ 2.5Watts Operating Temperature 0° C to + 50° C Operating Humidity 5%-95%, Non-condensing

Downloadable Documents

Thinity Caputre & Analyze

Model: 26100-222 Shipping Weight: 1.5lbs

Add to Cart: 1

Add to Cart

Copyright © 2008 Aven, Inc. 4595 Platt Road Ann Arbor, MI 48104 734-973-0099 st