



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Ultra-Flexible Silicone Rubber Wire UL 3212 150°C 600V

Daburn Ultra-Flexible Silicone Rubber Wire, has high temperature resistance and high flexibility due to silicone rubber insulation and high strand count conductors. Applications include whole sealed cooking appliances, lighting equipment, computers, electronic equipment, internal combustion engines and mercury switch leads. This wire meets UL Style 3212.

Description: Single conductor stranded tinned copper insulated with .045" silicone rubber insulation. This construction allows for a uniform, flexible, concentric, quality construction.

Operating Temperature: -40°C to +150°C

Voltage Rating: 600 Volts UL (Spark voltage 6,000 V)

FT2 Flame Rating.

This series is RoHS compliant.

Catalog Number	AWG	Strand	Nom. Wall		Nom. O.D.		Resistance dc at 20°C Ohm/mft	Nom. Wt. lbs./mft
			Inches	mm	Inches	mm		
2617/10	10	105/30	.045	1.15	.207	5.30	1.08	46.69
2617/12	12	65/30	.045	1.15	.183	4.66	1.72	32.26
2617/14	14	41/30	.045	1.15	.165	4.20	2.73	23.21
2617/16	16	55/33	.045	1.15	.155	3.93	4.45	17.75
2617/18	18	34/33	.045	1.15	.142	3.61	7.06	13.56
2617/20	20	19/33	.045	1.15	.132	3.35	11.2	10.69
2617/22	22	17/34	.045	1.15	.124	3.16	18.1	8.84
2617/24	24	7/32	.045	1.15	.114	2.90	28.7	7.59
2617/26	26	7/34	.045	1.15	.110	2.80	45.8	6.73

Standard Put-Ups: 50 feet, 100 feet, 500 feet, 1,000 feet

Colors Available: Black, Red, White, Green, Yellow, Blue, Brown, Grey, Violet, Orange