



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



APPROVAL SHEET

Customer: _____

Customer P/N: _____

Description: USB WIFI +Bluetooth dongle

Part No.: 802.11N 150M and Bluetooth 2.1+EDR

Customer Approval	Checked By	Issued By

USB WIFI +Bluetooth dongle

A .WIFI PART

1. Introduction

The RT5370 is a cost-effective, highly integrated USB Wi-Fi single chip containing an 802.11n MAC and baseband, a 2.4 GHz RF, PA, LNA and T/R switch on a single die. It supports a 150 Mbps PHY data rate and fully complies with 802.11b/g/n specifications, providing feature-rich wireless connectivity at high standards, and delivering reliable throughput from an extended distance. Optimized RF architecture and baseband algorithms provide superb performance with low power consumption.

Product Features

- **1T1R 2.4 GHz with 150 Mbps PHY data rate**
- **USB2.0 interface**
- **CMOS single chip with RF (PA, LNA, T/R SW, and diversity SW), Baseband, and MAC integration**
- **QoS: WMM & WMM-PS support**
- **Multiple BSSID support**
- **Uses digital CMOS technology exclusively, minimizing power consumption and cost while maximizing reliability**
- **Extended tuning range for worldwide use Dynamic Frequency Selection/Transmit Power Control (DFS/TPC) for international operation**
- **Cisco CCX 5.0 support**
- **Connect without wires at speeds up to 150Mbps**

- **Based on IEEE 802.11 b/g/n DRAFT standard wireless protocol-Wi-Fi certified.**
- **Compatible with the increasing number of Public Access facilities.**
 - **Low Power usage with Advanced Power Management**
- **Maximum likelihood Decoding support**
- **Security: WEP/TKIP/AES/WPA/WPA2/WAPI**

Application

- **Personal computer**
- **Laptop computer**
- **TV over IP (IPTV)**
- **Voice over IP(VoIP)**
- **Higher data rate wireless broadband access**
- **Network and online gaming**
- **Audio and video streaming and transfer**
- **PC file and application sharing**

3. General Specifications

Model Name	
Product Description	USB 2.0 802.11N Wireless 150M
WLAN Standard	IEEE 802.11 b/g/n ,Wi-Fi compliant
Host Interface	USB 2.0
Major Chipset	Ralink RT5370L
Operating Conditions	
Voltage	USB 5V
Temperature	-10~70℃
Humidity Non-Operating	90% RH non-condensing (12 months among 0~40℃)
Electrical Specification	
Frequency Range	2.4~2.4835GHZ
Spread Spectrum	DSSS
Transmission Distance	300m(The transmission speed may vary according to the environment)
Data Rate	11b:1/2/5.5/11Mbps 11g:6/9/12/24/36/48/54Mbps
Transmit power	15dbm
Data security	64/128/152bitWEP,WPA/WPA2,WPA-PSK/WPA2-PSK(TKIP /AES)
Receiver Sensitivity	150M:-68dbm@10%PER
	135M: -68dbm@10%PER
	54M:-68dbm@10%PER
	11M:-83dbm@10%PER
	6M:-86dbm@10%PER
	1M:-90dbm@10%PER
Environment	Storage Temperature:-40~70℃(-40°F ~158°F)
	Relative humidity:10%-90%

	Non-condensing
	Storage Humidity:5%~95%
	Non-condensing
Modulation Type	OFDM/CCK/16-QAM/64-QAM
Operating System	Window XP,XP-64 Windows7, 32/64,WIN 2000,Vista

4. Power Consumption

Mode	Status	Current (mA) @5V	Note
QA	Idle	89	
	RX	117	54Mbps,CH1
		117	MCS15, 20MHz,CH1
		137	MCS15, 40 MHz,CH3
	TX	173	11Mbps @ 17dBm,CH1
		155	54Mbps @ 13.9dBm, 11g,CH1
		155	MCS7, 20MHz,14dB,CH1
		166	MCS7, 40MHz,CH7
OS	LINK(S0)	102(20M)/120(40M)	
	RX	113	20MHz
		144	40 MHz
	TX	148	20MHz
		152	40 MHz
	SUSPEND	2	
	UNCONFIGURED	59	
	POWER SAVE MODE	52	DTIM=100ms
47		DTIM=300ms	
RADIO OFF	52		

B. BLUETOOTH PART

FEATURES

- *Bluetooth 2.1 compliant with enhanced data rate support
- *Class 2 capable with built-in PA
- *Programmable output power control meets Class1, Class2 or Class3 requirements
- *Supports H4DS and WCS
- *Use supply voltages up to 5.5V
- *Internal OR gate TCXO control
- *Fractional-N synthesizer supports frequency references from 12 MHz to 40 MHz
- *Automatic frequency detection for standard crystal and TCXO values
- *Lower power consumption
- *Supports mobile and PC applications without external memory

5. SPECIFICATIONS

5.1 General Specification

ITEMS	SPECIFICATION
Supply Voltage	USB Interface Level VDD: 5V+/-0.1V
Carrier Frequency	2402MHz to 2480MHz
Modulation Method	GFSK, 1Mbps, 0.5BT Gaussian
Data Rate (MAX)	1M Asynchronous: 723.2/57.6kbps Synchronous: 433.9kbps
	2M Asynchronous: 1448.4/115.2kbps Synchronous: 864.7kbps
	3M Asynchronous: 2178.1/177.1kbps ynchronous: 1306.9kbps
Transmission Power	-.4dBm to +2 dBm; Power control 6 stage
Hopping	1600hops/sec, 1MHz channel space
Receiving Signal Range	-.88dBm to -20 dBm

5.2. Electrical Characteristics

5.2.1 Receiver RF Specifications

ITEMS	Mode and Conditions	Minimum	Typical ^f	Maximum	Unit
Frequency range	-	2042	-	2480	MHz
	GFSK, 0.1%BER, 1 Mbps	-	-86	-84	dBm
RX sensitivity ^c	pi/4-DQPSK, 0.01%BER 2Mbps	-	-86	-84	dBm
	8-DPSK, 0.01%BER, 3Mbps	-	-82	-80	dBm
Input IP3	-	-16	-	-	dBm
Maximum input	-	-	-	-10	dBm
Interference Performance					
C/I cochannel	GFSK, 0.1%BER	-	-	2	dBm
C/I 1 MHz adjacent channel	GFSK, 0.1%BER	-	-	0	dBm
C/I 2 MHz adjacent channel	GFSK, 0.1%BER	-	-	-30	dBm
C/I 3 MHz adjacent channel	GFSK, 0.1%BER	-	-	-40	dBm
C/I Image channel	GFSK, 0.1%BER	-	-	-9	dBm
C/I 1 MHz adjacent to image channel	GFSK, 0.1%BER	-	-	-20	dBm
C/I cochannel	pi/4-DQPSK, 0.1%BER	-	-	13	dBm
C/I 1 MHz adjacent channel	pi/4-DQPSK, 0.1%BER	-	-	0	dBm
C/I 2 MHz adjacent channel	pi/4-DQPSK, 0.1%BER	-	-	-30	dBm
C/I 3 MHz adjacent channel	8-DPSK, 0.1%BER	-	-	-40	dBm
C/I Image channel	pi/4-DQPSK, 0.1%BER	-	-	-7	dBm
C/I 1 MHz adjacent to image channel	pi/4-DQPSK, 0.1%BER	-	-	-20	dBm
C/I cochannel	8-DPSK, 0.1%BER	-	-	21	dBm
C/I 1 MHz adjacent channel	8-DPSK, 0.1%BER	-	-	5	dBm
C/I 2 MHz adjacent channel	8-DPSK, 0.1%BER	-	-	-25	dBm
C/I 3 MHz adjacent channel	8-DPSK, 0.1%BER	-	-	-33	dBm
C/I Image channel	8-DPSK, 0.1%BER	-	-	0	dBm
C/I 1 MHz adjacent to image channel	8-DPSK, 0.1%BER	-	-	-13	dBm
Out-of-Band Blocking Performance (CW)					
30 MHz to 2000 MHz,	0.1% BER	-	-10	-	dBm
2000 MHz to 2399 MHz	0.1% BER	-	-27	-	dBm
2498 MHz to 3000 MHz	0.1% BER	-	-27	-	dBm
3000 MHz to 12.75 GHz	0.1% BER	-	-10	-	dBm

5.2.2 Transmitter RF Specifications

ITEMS	Mode and Conditions	Minimum	Typicalf	Maximum	Unit
Frequency range	-	2042	-	2480	MHz
Output power - Class 2	-	-2	1	4	dBm
Output power - Class 1, GFSK	-	-	TBD	NC	dBm
Output power - Class 1, EDR	-	-	TBD	NC	dBm

In-Band Spurious Emission

:+/-500 kHz	-	-	-	-20	dBc
1.0 MHz < M - N < 1.5 MHz (EDR only)	-	-	-	-26	dBc
1.5 MHz < M - N < 2.5 MHz (EDR only)	-	-	-	-20	dBc
M - N ≥ 2.5 MHz (EDR only)	-	-	-	-40	dBc

Out-of-Band Spurious Emission

30 MHz to 1 GHz	-	-	-80	-36	dBm
1 GHz to 12.75 GHz	-	-	-	-30	dBm
1.8 GHz to 1.9 GHz	-	-	-80	-47	dBm
5.15 GHz to 5.3 GHz	-	-	-90	-36	dBm

Frequency Drift

DH1 packet	-	-	±20	±25	kHz
DH3 packet	-	-	±20	±40	kHz
DH5 packet	-	-	±20	±40	kHz
Drift rate	-	-	10	20	kHz/50 μs