## imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



NOTES:	265104-01-XX.XX	REVISIONS	
	DRAWING NO. REV	DESCRIPTION	DATE ECO APPR
1. PACKAGE CABLE ASSEMBLY IN BAG. TAG IN BAG WITH "AMPHENOL CONNEX, 265104-01-XX.XX AND DATE CODE".	THIRD ANGLE PROJ. 🕀 🖯 A	RELEASE TO MFG.	23-Nov-10 KR
2. CABLE ASSEMBLY TO BE 100% TESTED FOR HI-POT, CONTINUITY, SHORTS AND OPEN.	В	009-881-205 W AS 009-881-005	28-Nov-12 2406 MG
			SCALE 0.750
	LENGTH "L" (SEE TABLE)		►
TYP(2) ( CONNEX NUMBER 265104-01-06.00 265104-01-12.00 265104-01-12.00 265104-01-36.00 • ADDITIONAL LE DESIRED LENSTH	0         6±0.25         0.75 MIN           0         12±0.25         0.75 MIN           0         18±0.25         0.75 MIN           0         24±0.5         0.75 MIN	ΓE	(3) TYP(2)
DESIGN REQUIREMENTS:			
FREQUENCY TO GHZ X CONTINUITY		[	
		009-954-341 A/R 3 HEAT S	SHRINK TUBE BLACK
VSWR : 1 MAX X HI-POT : 300 VRMS			
VSWR     : 1 MAX     X HI-POT : 300 VRMS			COAX CABLE BLACK
VSWR     : 1 MAX     X HI-POT : 300 VRMS       INS. LOSS     dB MAX     OTHER		262103 2 1 R/A MMCX 3	
INS. LOSS dB MAX       OTHER         UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:       MATERIAL         2 PLACE DECIMAL       3 PLACE DECIMAL       ANGLES         ±.015       (0,381 mm)       ±.005       (0,127 mm)       ± 1°         NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, aranting       REFERENCE	DRAWN DATE KARTHIK R 23-Nov-10 ENGINEER DATE KARTHIK R 23-Nov-10 APPROVED DATE	262103     2     1     R/A     MMCX       PART NUMBER     QTY     ITEM     DESC       TITLE     R/A     MMCX     STR     CRIMP     PLUG     TO       R/A     MMCX     STR     CRIMP     PLUG,       USING     RG-316     COAX     CABLE,       XX     XX     LENGTH	COAX CABLE BLACK STR CRIMP PLUG
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES ±.015 (0,381 mm) ±.005 (0,127 mm) ± 1° NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or PLACE DECIMAL 3 PLACE DECIMAL ANGLES # .015 (0,381 mm) ± .005 (0,127 mm) ± 1° MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL REFERENCE	KARTHIK R23-Nov-10ENGINEERDATEKARTHIK R23-Nov-10	262103       2       1       R/A MMCX STR         PART NUMBER       QTY       ITEM       DESC         TITLE       R/A       MMCX       STR       CRIMP       PLUG       TO         R/A       MMCX       STR       CRIMP       PLUG       TO         R/A       MMCX       STR       CRIMP       PLUG       TO         USING       RG-316       COAX       CABLE,       XX.XX"       LENGTH         DWG       SIZE       DRAWING       NO.	COAX CABLE BLACK STR CRIMP PLUG CRIPTION FINISH Amphenol Connex SCALE: 3.0:1 SHEET 1 OF 1