imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Item # 26700-103-00, Macro Zoom Video Inspection System with Standard Stand



- 6X Macro Zoom Lens
- Focus Mount with Coarse and Fine Focus
- Standard Stand with 10 threaded holes. Allows you to fixture your part if necessary. Size of base 279 x 330 mm (11"x 13") with stainless steel post 406.5mm (16") tall
- VGA 1.3M HD color camera with built in SD Card. Camera. For more information on the camera, Click Here



A PC is NOT required for image processing, however you will require a PC monitor (19 in or above) for viewing images. Specifications w Close Up Lens with a 15 in monitor

Working Distance	FOVmm@ Low Mag	FOVmm@High Mag	Magnification Range
5″	25.9 x19.5	4.3 x 3.2	12x to 71x
7"	38.9 x 29.2	6.5 x 4.9	8x to 47x
8"	45.5 x 34	7.6 x 5.7	7x to 40x
10"	58.3 x 43.7	9.7 x 7.3	5x to 31x

SPECIFICATIONS

Magnification	12x-71x
Field of View	25.9 to 4.3 mm
Working Distance	127 mm