



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Inline function terminal - IB IL 24 IOL 4 DI 12-PAC - 2692717

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline IO-Link master, complete with accessories (connector and labeling field), 4 IO-Link ports, 12 digital inputs, 24 V DC, 2, 3-wire connection method

### Product description

The device serves to connect IO-Link devices.

### Product Features

- Optional use of the IO-Link ports in SIO mode as standard inputs or standard outputs
- 4 type A IO-Link ports
- Connections for 12 digital sensors



### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	240.0 GRM
Custom tariff number	85389091
Country of origin	Germany

### Technical data

#### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

#### Dimensions

Width	48.8 mm
Height	119.8 mm
Depth	71.5 mm

#### Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C

# Inline function terminal - IB IL 24 IOL 4 DI 12-PAC - 2692717

## Technical data

### Ambient conditions

Permissible humidity (operation)	10 % ... 95 % (according to DIN EN 61131-2)
Permissible humidity (storage/transport)	10 % ... 95 % (according to DIN EN 61131-2)
Air pressure (operation)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Degree of protection	IP20

### General

Weight	200 g
Note on weight specifications	with connectors
Mounting type	DIN rail
Protection class	III, IEC 61140, EN 61140, VDE 0140-1
Test section	24 V supply $U_S$ (IO-Link and digital inputs) / functional earth ground 500 V DC 50 Hz 1 min
	24 V supply $U_S$ (IO-Link and digital inputs) / 7.5 V supply (bus logic) 500 V DC 50 Hz 1 min
	7.5 V supply (bus logics) / functional earth ground 500 V DC 50 Hz 1 min
Diagnostics messages	Short-circuit of a digital output in the SIO mode Yes
	Sensor supply short-circuit No
	Sensor supply overload No

### Interfaces

Fieldbus system	Lokalbus
Designation	Inline local bus
Connection method	Inline data jumper
Transmission speed	500 kBit/s

### Power supply for module electronics

Connection method	via potential routing
-------------------	-----------------------

### Inline potentials

Communications power $U_L$	7.5 V (via voltage jumper)
Current consumption from $U_L$	max. 100 mA
Segment supply voltage $U_S$	24 V DC (nominal value)
Current consumption from $U_S$	max. 2 A (with load and port supply)
	max. 52 mA (without load)

### Digital inputs

Input name	Digital inputs
Connection method	Inline connector
	2, 3-wire

## Inline function terminal - IB IL 24 IOL 4 DI 12-PAC - 2692717

### Technical data

#### Digital inputs

Number of inputs	12 (EN 61131-2 type 1)
Input voltage range "0" signal	< 5 V (typ.)
Input voltage range "1" signal	> 11 V (typ.)
Nominal input current at $U_{IN}$	2.2 mA
Delay at signal change from 0 to 1	3 ms
Delay at signal change from 1 to 0	3 ms

### Classifications

#### eCl@ss

eCl@ss 4.0	27250302
eCl@ss 4.1	27250302
eCl@ss 5.0	27250302
eCl@ss 5.1	27242604
eCl@ss 6.0	27242604
eCl@ss 7.0	27242604
eCl@ss 8.0	27242608

#### ETIM

ETIM 2.0	EC001430
ETIM 3.0	EC001599
ETIM 4.0	EC001599
ETIM 5.0	EC001599


#### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

### Drawings

# Inline function terminal - IB IL 24 IOL 4 DI 12-PAC - 2692717

Connection diagram



Dimensioned drawing

