

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Optical element - PSD-S OE LED RD - 2700107

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



LED permanent light element, 24 V AC/DC, red

Why buy this product

- Minimum LED service life of 50,000 h
- ☑ IP65 degree of protection



Key Commercial Data

Packing unit	1 STK
GTIN	4 046356 491082
GTIN	4046356491082

Technical data

Dimensions

Diameter	70 mm
Height	65.5 mm

Ambient conditions

Ambient temperature (operation)	-30 °C 50 °C
Degree of protection	IP65, when installed or with cover

General

Material	Polycarbonate PC
Calotte color	red
Weight	58 g
Mounting position	any

08/19/2018 Page 1 / 3



Optical element - PSD-S OE LED RD - 2700107


Technical data

General

Assembly instructions	Rubber seal pre-installed for each element		
Electrical data			
Input voltage	24 V AC/DC		
Maximum inrush current	max. 500 mA		
Current consumption	max. 40 mA		
Service life, electrical	max. 100,000 h		
Operating time	100 %		
Optical signal type	Permanent light		
Approvals / conformities			
Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU		
Standards and Regulations			
Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU		
Environmental Product Compliance			
REACh SVHC	Lead 7439-92-1		
China RoHS	Environmentally Friendly Use Period = 50		
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"		

Drawings

Dimensional drawing



Approvals

Approvals



Optical element - PSD-S OE LED RD - 2700107

Approvals

Approvals UL Listed / cUL Listed / EAC	EAC / cULus Listed		
Ex Approvals			
Approval details			
UL Listed	LISTED	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 123528
cUL Listed	c UL	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 123528
EAC	EAC		EAC-Zulassung
EAC	EAC		RU *- DE.A*30.B.00237
cULus Listed	C UL) US		

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com