# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Extract from the online catalog

### **FL MGUARD SMART/533 VPN**

Order No.: 2700181



http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2700181

Router with intelligent Firewall, Stateful Inspection Firewall for optimum safety and extremely simple configuration, VPN as per IPsec standard, hardware encryption with up to 70 Mbps, in the portable housing, power supply via USB, 533-MHz processor cycle frequency

#### **Commercial data**

GTIN (EAN)

GTIN (EAN)	4 046356 498074
Note	Made-to-order
sales group	K006
Pack	1 pcs.
Customs tariff	85176200

#### Product notes

WEEE/RoHS-compliant since: 03/05/2009



#### http://

www.download.phoenixcontact.com Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

#### **Technical data**

#### Interfaces

Interface	Ethernet
No. of ports	2
Type of connection	RJ45

Transmission physics	Ethernet in RJ45 twisted pair
Transmission speed	10/100 MBit/s
Transmission length	100 m (per segment)
Signal LEDs	Supply voltage, data transmission, error, link, activity
Function	
Management	Web-based Management, SNMP
Supported browsers	HTTPS support required
Processor	533 MHz
Supply voltage	
Supply voltage	5 V DC (from USB interface)
General data	100 -
Weight	160 g
Width	77 mm
	27 mm
Depth	115 mm
Degree of protection	IP30
Ambient temperature (operation)	0 °C 40 °C
Ambient temperature (storage/transport)	-20 °C 70 °C
Permissible humidity (operation)	20 % 90 % (no condensation)
Security functions	
Virtual private network (VPN) throughput	Up to 70 Mbps
Number of VPN tunnels	10 (Up to 250 with license possible)
Encryption methods	DES, 3DES, AES-128, -192, -256
Internet Protocol Security (IPsec) mode	ESP-Tunnel / ESP-Transport
	ESP-Tunnel / ESP-Transport X.509v3 certificates with RSA or PSK
Authentication	•
Authentication Data integrity 1:1 Network Address Translation (NAT) in the	X.509v3 certificates with RSA or PSK
Authentication Data integrity 1:1 Network Address Translation (NAT) in the VPN	X.509v3 certificates with RSA or PSK MD5, SHA-1
Authentication Data integrity 1:1 Network Address Translation (NAT) in the VPN Firewall data throughput	X.509v3 certificates with RSA or PSK MD5, SHA-1 Supported
Internet Protocol Security (IPsec) mode Authentication Data integrity 1:1 Network Address Translation (NAT) in the VPN Firewall data throughput Firewall rules Filtering	X.509v3 certificates with RSA or PSK   MD5, SHA-1   Supported   Up to 99 Mbps
Authentication Data integrity 1:1 Network Address Translation (NAT) in the VPN Firewall data throughput Firewall rules	X.509v3 certificates with RSA or PSK   MD5, SHA-1   Supported   Up to 99 Mbps   Configurable stateful inspection firewall

#### Accessories

Item	Designation	Description
Cable/conductor		
2832250	FL CAT5 PATCH 0,3	Patch cable, CAT5, assembled, 0.3 m
2832263	FL CAT5 PATCH 0,5	Patch cable, CAT5, assembled, 0.5 m
2832276	FL CAT5 PATCH 1,0	Patch cable, CAT5, assembled, 1.0 m
2832221	FL CAT5 PATCH 1,5	Patch cable, CAT5, assembled, 1.5 m
2832629	FL CAT5 PATCH 10,0	Patch cable, CAT5, assembled, 10.0 m
2832289	FL CAT5 PATCH 2,0	Patch cable, CAT5, assembled, 2.0 m
2832292	FL CAT5 PATCH 3,0	Patch cable, CAT5, assembled, 3.0 m
2832580	FL CAT5 PATCH 5,0	Patch cable, CAT5, assembled, 5.0 m
2832616	FL CAT5 PATCH 7,5	Patch cable, CAT5, assembled, 7.5 m
2891369	FL CAT6 PATCH 12,5	Patch cable, CAT6, pre-assembled, 12.5 m
2891372	FL CAT6 PATCH 15,0	Patch cable, CAT6, pre-assembled, 15.0 m
2891576	FL CAT6 PATCH 20,0	Patch cable, CAT6, pre-assembled, 20.0 m
General		
2744788	FL MC 10BASE-T/FO G850	Fiber optic converter, for converting 10Base-T to multimode glass fiber, (850 nm), B-FOC (ST <sup>®</sup> ) FO connection, supply 24 V DC
2891165	FL PF 2TX CAT5E	Patch field with two RJ45 CAT5e network connections
2891178	FL PF 8TX CAT5E	Patch field with eight RJ45 CAT5e network connections
2832991	FL RJ45 PROTECT CAP	Dust protection caps for RJ45 female connector
Plug/Adapter		
2744571	FL PLUG RJ45 GN/2	RJ45 connector, shielded, with bend protection sleeve, 2 pieces, green for crossed cables, for assembly on site. For connections that are crossed, it is recommended that the connector set with green bend protection sleeves is used.
2744856	FL PLUG RJ45 GR/2	RJ45 connector, shielded, with bend protection sleeve, 2 pieces, gray for straight cables, for assembly on site. For connections that are not crossed, it is recommended that you use the connector set with gray bend protection sleeve.
Tools		
2744869	FL CRIMPTOOL	Crimping pliers, for assembling the RJ45 connectors FL PLUG RJ45, for assembly on site

#### Address

PHOENIX CONTACT Deutschland GmbH Flachsmarktstr. 8 32825 Blomberg,Germany Phone +49 5235 3 12000 Fax +49 5235 3 41200 http://www.phoenixcontact.de



© 2011 Phoenix Contact Technical modifications reserved;