



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Controller - AXC 3050 - 2700989

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Axiococontrol for the direct control of Axioline F I/Os. With 3 Ethernet interfaces for the additional connection of distributed I/Os via PROFINET, Modbus TCP or TCP/IP. Programming according to IEC 61131-3. Includes connector plug and marking field.

Product Description

The AXC 3050 modular controller for the Axioline I/O system is fast, robust, and easy, i.e., it is consistently designed for maximum performance, easy handling, and use in harsh industrial environments.

Why buy this product

- ✓ PROFINET controller and PROFINET device
- ✓ Modbus/TCP-Client
- ✓ Numerous protocols supported such as: http, https, FTP, SNMP, SMTP, SQL, MySQL, DCP, etc.
- ✓ Up to 63 AXIO I/O modules can be mounted side by side
- ✓ Integrated UPS for targeted shutdown of the application
- ✓ Programming and configuration via USB
- ✓ Web server HTML5 and JAVA
- ✓ SD card up to 2 GB as optional plug-in parameterization memory
- ✓ 3x Ethernet interfaces
- ✓ Increased resistance to EMI
- ✓ Extended temperature range of -25°C ... +60°C
- ✓ Integrated technology functions such as fast counters, incremental encoder inputs, and event tasks



Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	460.000 g
Custom tariff number	85371099
Country of origin	Germany

Controller - AXC 3050 - 2700989

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	100 mm
Height	125.9 mm
Depth	74 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 60 °C (up to 2000 m above mean sea level)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Ambient temperature (assembly)	-5 °C ... 60 °C
Permissible humidity (operation)	5 % ... 95 % (according to DIN EN 61131-2)
Permissible humidity (storage/transport)	5 % ... 95 % (according to DIN EN 61131-2)
Air pressure (operation)	70 kPa ... 106 kPa (up to 3000 m above mean sea level)
Air pressure (storage/transport)	58 kPa ... 106 kPa (up to 4500 m above sea level)
Shock	30g, 11 ms period, half-sine shock pulse, according to IEC 60068-2-27
Vibration (operation)	5g

Control system

Programming tool	PC WORX
Diagnostics tool	DIAG+

Mechanical design

Diagnostics display	No
Controller redundancy	No

Data interfaces

Interface	Axioline F local bus
Number	1
Connection method	Bus base module
Transmission speed	100 MBit/s
Interface	Parameterization/operation/diagnostics
Number	1
Connection method	Micro USB type B
	USB type A, socket
Interface	Ethernet
Number	3
Connection method	RJ45 socket

Controller - AXC 3050 - 2700989

Technical data

Data interfaces

Transmission speed	10/100 MBit/s
--------------------	---------------

Power supply

Typical current consumption	typ. 408 mA (without I/Os and $U_L = 24\text{ V}$)
Max. current consumption	max. 976 mA (with 2 A at U_{Bus} for the I/Os and $U_L = 24\text{ V}$)
Supply voltage	24 V DC
Supply voltage range	19.2 V DC ... 30 V DC
Residual ripple	$\pm 5\%$
Power dissipation	max. 9.8 W

Fieldbus function

Number of supported devices	max. 63
Number of local bus devices that can be connected	max. 63 (observe current consumption)

General data

Processor	Intel® Atom™ E660 1.3 GHz
-----------	---------------------------

Direct I/Os

Without analog input	yes
Without analog output	yes
Without pulse direction output	yes
Without counter input	No
Input name	Counter input for 24 V signals
Number of inputs	max. 2 (via any digital inputs of the Axioline F modules)
Input frequency	max. 100 kHz (with AXL F DI16/1 HS 1H module)

IEC 61131 runtime system

Programming tool	PC WORX
Program memory	4 Mbyte
Mass storage	8 Mbyte
Retentive mass storage	128 kByte
Number of control tasks	16
Realtime clock	Yes

Standards and Regulations

Shock	30g, 11 ms period, half-sine shock pulse, according to IEC 60068-2-27
Vibration (storage/transport)	5g
Vibration (operation)	5g
Shock (operation)	10g (Bump endurance test according to EN 60068-2-29)

Controller - AXC 3050 - 2700989

Classifications

eCl@ss

eCl@ss 4.0	27240602
eCl@ss 4.1	27240602
eCl@ss 5.0	27242589
eCl@ss 5.1	27242590
eCl@ss 6.0	27242590
eCl@ss 7.0	27242590
eCl@ss 8.0	27242207
eCl@ss 9.0	27242207

ETIM

ETIM 3.0	EC001045
ETIM 4.0	EC001435
ETIM 5.0	EC000236

UNSPSC

UNSPSC 6.01	81111810
UNSPSC 7.0901	81111810
UNSPSC 11	81111810
UNSPSC 12.01	81111810
UNSPSC 13.2	81111810

Approvals

Approvals

Approvals

EAC / UL Listed / cUL Listed / cULus Listed

Ex Approvals

Approval details

EAC EAC-Zulassung

Controller - AXC 3050 - 2700989

Approvals

UL Listed  <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm> FILE E 238705

cUL Listed  <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm> FILE E 238705

cULus Listed 

Accessories

Accessories

Drivers and interfaces

Software - AX OPC SERVER - 2985945



AX OPC SERVER, communication interface for OPC-capable visualization with PC WORX-based controls.

Parameterization memory

Memory - SD FLASH 512MB - 2988146



Program and configuration memory, plug-in, 512 Mbyte.

Memory - SD FLASH 512MB APPLIC A - 2701799



Program and configuration memory, plug-in, 512 MB with license key for functional block libraries, e.g., for: SNMP, SQL, wireless, motion functions, etc.

Controller - AXC 3050 - 2700989

Accessories

Memory - SD FLASH 512MB PDPI PRO - 2701801



Program and configuration memory, plug-in, 512 MB with license key for licensing the PDPI - PRO functional block for precise multi-channel controllers with self-optimization, additional functions: e.g., for setpoint processing, for heating and cooling functions.

Memory - SD FLASH 512MB PDPI BASIC - 2701800



Program and configuration memory, plug-in, 512 MB with license key for licensing the PDPI - BASIC functional block for precise multi-channel controllers with self-optimization, e.g., for heating and cooling functions or hydraulic movements.

Program / configuration memory - SD FLASH 2GB - 2988162



Program and configuration memory

Program / configuration memory - SD FLASH 2GB APPLIC A - 2701190



Program and configuration memory, plug-in, 2 Gbytes with license key for function block libraries, e.g., for: SNMP, SQL, wireless, motion functions, etc.

Programming

Software - PC WORX DEMO - 2985725



Software package for PC-based automation solutions, PC WORX DEMO, contains all 5 IEC languages, with MSFC compiler, max. 16 bytes input and output data

Controller - AXC 3050 - 2700989

Accessories

Software - PC WORX BASIC LIC - 2985275



Software package for PC-based automation solutions, PC WORX BASIC license, contains all 5 IEC languages, without MSFC compiler, max. 2048 byte input and output data, version-specific license key

Software - PC WORX PRO LIC - 2985385



Software package for PC-based automation solutions, PC WORX PRO license, contains all 5 IEC languages, with MSFC compiler, max 128 kB input and output data, version-specific license key

Programming cable

Connecting cable - CAB-USB A/MICRO USB B/2,0M - 2701626



Connecting cable, for connecting the controller to a PC for PC Worx and LOGIC+, USB A to micro USB B, 2 m in length.

Spare parts

Bus connector - AXC BS - 2701582



Axiocontrol bus base module for AXC 3xxx