

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Replacement electronics module - IB STME 24 AO 4/EF - 2701954

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



INTERBUS-ST analog output module, 4 outputs, 0 - 10 V, ±10 V, 0 - 20 mA, 4 - 20 mA, comprising: Module electronics only



Key Commercial Data

Packing unit	1 STK
GTIN	4 046356 895736
GTIN	4046356895736

Technical data

Note

area	Utilization restriction	EMC: class A product, see manufacturer's declaration in the downloa area
------	-------------------------	--

Ambient conditions

Ambient temperature (operation)	-25 °C 55 °C
Ambient temperature (storage/transport)	-25 °C 70 °C
Permissible humidity (operation)	10 % 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % 95 % (non-condensing)
Air pressure (operation)	80 kPa 106 kPa (up to 2000 m above sea level)
Air pressure (storage/transport)	80 kPa 106 kPa (up to 2000 m above sea level)
Degree of protection	IP20

General

Mounting type	DIN rail
Net weight	241 g
Operating mode	Process data mode with 4 words
Diagnostics messages	Failure of the internal I/O supply I/O error message sent to the bus coupler
	F1 fuse failure I/O error message sent to the bus coupler



Replacement electronics module - IB STME 24 AO 4/EF - 2701954

Technical data

General

	I/O supply failure I/O error message sent to the bus coupler	
Interfaces		
Designation	ST local bus	
Connection method	ST local bus connector	
Transmission speed	500 kbps	
Transmission physics	Copper	

Power supply for module electronics

Connection method	ST local bus connector
Designation	Communications power
Supply voltage	9 V DC (from the ST local bus)
Current consumption	typ. 54 mA
	max. 80 mA
Power consumption	typ. 0.5 W

Analog outputs

Number of outputs	4 (Voltage or current)
Connection technology	2, 3-conductor
Output name	Analog outputs
D/A conversion time	max. 1 ms (incl. slew rate)
D/A resolution	12 bit
Type of protection	Transient protection
Protective circuit/component	Suppressor diode
Representation of output values	16 bit two's complement
Current output signal	0 mA 20 mA (SF and SF4 mode)
	4 mA 20 mA (Mode SF4)
Load/output load current output	to 500 Ω
Voltage output signal	-10 V 10 V (Mode BP)
	0 V 10 V (SF and SF4 mode)
Load/output load voltage output	> 2 kΩ

Electrical isolation

Test section	Bus/Outputs 500 V AC 50 Hz 1 min.
	Supply voltage/Outputs 500 V AC 50 Hz 1 min.
	Supply voltage/Ground conductor 500 V AC 50 Hz 1 min.
	I/O voltage/Ground conductor 500 V AC 50 Hz 1 min.

Standards and Regulations

Protection class	III, IEC 61140, EN 61140, VDE 0140-1

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
------------	---



Replacement electronics module - IB STME 24 AO 4/EF - 2701954

Technical data

Environmental Product Compliance

No hazardous substances above threshold values

Phoenix Contact 2018 @ - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com