

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









# Optical element - PSD-S OE LED MC - 2702090

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



LED permanent light element, 24 V DC, 7 colors

#### **Product Description**

The multi-colored LED permanent light element is designed for signaling machine states, for example. The optical element can light up red, green, yellow, blue, white, violet, and turquoise. The color is selected via different combinations of the control signals present at the signal tower connection element.

#### Why buy this product

- 7 colors in one element
- High light and color intensity
- Minimum LED service life of 50,000 h
- ☑ IP65 degree of protection



# **Key Commercial Data**

Packing unit	1 STK
GTIN	4 046356 943185
GTIN	4046356943185

### Technical data

#### **Dimensions**

Diameter	70 mm
Height	65.5 mm

#### Ambient conditions

Ambient temperature (operation)	-20 °C 50 °C	
Degree of protection	IP65, when installed or with cover	

#### General



# Optical element - PSD-S OE LED MC - 2702090

# Technical data

# General

Material	Polycarbonate PC
Calotte color	clear
Color	red
	green
	yellow
	blue
	white
	violet
	turquoise
Note color	In an unconnected state the calotte is clear, once connected it is illuminated according to the colors specified in the control.
Weight	63 g
Mounting position	any
Assembly instructions	Rubber seal pre-installed for each element

#### Electrical data

Input voltage	24 V DC
Maximum inrush current	max. 500 mA
Current consumption	120 mA
Service life, electrical	max. 50,000 h
Operating time	100 %
Optical signal type	Permanent light

### Approvals / conformities

Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
-------------------------------	---

# Standards and Regulations

Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
-------------------------------	---

# **Environmental Product Compliance**


China RoHS	Environmentally Friendly Use Period = 50	
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"	

# Drawings



# Optical element - PSD-S OE LED MC - 2702090

# Dimensional drawing



cULus Listed

Approvals			
Approvals			
Approvals			
UL Listed / cUL Listed / cULu	us Listed		
Ex Approvals			
Approval details			
UL Listed	LISTED	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 123528
cUL Listed	CUL	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 123528



Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300

Fax +49 5235 3 41200

http://www.phoenixcontact.com