

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Antenna cable - RAD-PIG-RSMA/N-5 - 2702140

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Antenna cable, 5 m in length; N (male) -> RSMA (male), impedance 50 ohms



The illustration shows a version of the product

Key Commercial Data

| Packing unit | 1 pc |
|--------------------------------------|---------------|
| Weight per Piece (excluding packing) | 250.0 g |
| Custom tariff number | 85442000 |
| Country of origin | United States |

Technical data

Dimensions

| Fixed cable length | 5 m |
|--------------------|---------|
| External diameter | 4.95 mm |

Ambient conditions

| Ambient temperature (operation) | -40 °C 85 °C |
|---------------------------------|--------------|

General

| Connection method | RSMA (male) |
|------------------------|-------------|
| | N (male) |
| Cable type | 195 |
| Minimum bending radius | 12.70 mm |
| Frequency range | 900 MHz |
| | 2.4 GHz |
| | 5 GHz |
| Impedance | 50 Ω |

Attenuation

| 868 / 900 MHz | 2.02 dB |
|---------------|---------|
| 2.4 GHz | 3.32 dB |

10/29/2015 Page 1 / 2



Antenna cable - RAD-PIG-RSMA/N-5 - 2702140

Technical data

Attenuation

| 5 GHz | 4.83 dB |
|--------|---------|
| 5 5.12 | |

Classifications

eCl@ss

| eCl@ss 4.0 | 27230207 |
|------------|----------|
| eCl@ss 4.1 | 27250312 |
| eCl@ss 5.0 | 27242208 |
| eCl@ss 5.1 | 27061802 |
| eCl@ss 6.0 | 27242208 |
| eCl@ss 7.0 | 27242208 |

ETIM

| ETIM 2.0 | EC000019 |
|----------|----------|
| ETIM 3.0 | EC000019 |
| ETIM 4.0 | EC000019 |
| ETIM 5.0 | EC001682 |

Phoenix Contact 2015 @ - all rights reserved http://www.phoenixcontact.com