imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Electronic housing - ME 22,5 OT-1MSTBO SET - 2707741

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)

Upper part of housing, for COMBICON connection, single-level



Product Features

- ☑ Tool-free mounting
- Gold contacts for data transmission and power supply (125 V, 8 A)
- Low design width with a high number of positions
- ME...TBUS connector with 5 parallel contacts can be snapped onto DIN rails to save space
- Large assembly area
- When a device is unplugged from the system as a whole, the signal chain is not interrupted# Supply via standard MINI COMBICON plug
- Recessed labeling areas
- ☑ Same PCB geometry for all design widths
- Inflammability class V0 according to UL 94
- ☑ Fast mounting on DIN rails according to EN 60715
- Cost savings thanks to easy device production
- Material and part identification embossed on the housing (recyclability)
- optional BUS connection integrated in the housing, for either parallel or serial contacting
- Metal foot catch
- Functional earth ground contact (EMC) integrated in the housing base
- Electronic components can be partially removed

Key commercial data

Packing unit	11
Weight per Piece (excluding packing)	28.5 GRM
Custom tariff number	85369010
Country of origin	Germany

Technical data

General

Housing type	Upper part
Housing material	Polyamide



Electronic housing - ME 22,5 OT-1MSTBO SET - 2707741

Technical data

General

Color	green		
Ambient conditions			
Ambient temperature (operation)	-40 °C 105 °C		
Dimensions			
Constructional height	38.5 mm		
Width	22.5 mm		
Technical data			
Connection in acc. with standard	CUL		
Nominal voltage U _N	300 V		
Nominal current I _N	12 A		
AWG/kcmil	30-12		
Indicator1	CUL1		
Inflammability class according to UL 94	V0		
Number of positions	4		

Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC000886

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501



Electronic housing - ME 22,5 OT-1MSTBO SET - 2707741

Classifications

UNSPSC

UNSPSC 12.01		31261501		
UNSPSC 13.2		31261501		
Approvals				
Approvals				
pprovals				
IL Recognized / cUL Recognized / c	ULus Recognized			
Ex Approvals				
opprovals submitted				
Approval details				
UL Recognized SU				
cUL Recognized				
	В		D	
mm²/AWG/kcmil	30-12		30-12	
	12 A		10 A	
Nominal current IN Nominal voltage UN	250 V		300 V	

© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com