



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Daburn Electronics & Cable
 44 Richboynton Road
 Dover, NJ 07849

#2706 – #2714 DAFLEX Ultra-Flexible Miniature Shielded Cable

This series is suited for low voltage applications where flexibility is required; such as computer, bio-medical instruments, missiles, robotics, recorders and servers.

Description: Each conductor in the cable is ultra-flexible, finely stranded bare copper (tinned copper on 2752/5), covered overall with a thin, wall of color coded, soft, flexible PVC insulation. The conductors are cabled and covered with a TC braid shield (90% minimum coverage) and a soft flexible black PVC jacket. White is available to order.

Operating Temperature: -40°C to +105°C.

Operating Voltage: 200 Volts. 22 AWG & 24 AWG 600 Volts.

This series is RoHS Compliant.

Daburn Cat. No.	No. of Cond.	AWG	Strand.	Nom. Wall		Nom. Jacket		Nom. O.D.		Standard P-U	Shield Type
				IN	MM	IN	MM	IN	MM		
2714/2	2	38	17/50	.005	.127	.010	.254	.058	1.47	1000'	Braid TC
2714/3	3	38	17/50	.005	.127	.010	.254	.061	1.55	1000'	Braid TC
2714/4	4	38	17/50	.005	.127	.010	.254	.065	1.65	1000'	Braid TC
2714/5	5	38	17/50	.005	.127	.010	.254	.070	1.79	1000'	Braid TC
2713/2	2	36	25/50	.005	.127	.010	.254	.060	1.52	1000'	Braid TC
2713/3	3	36	25/50	.005	.127	.010	.254	.063	1.60	100', 1000'	Braid TC
2713/4	4	36	25/50	.005	.127	.010	.254	.068	1.73	100', 1000'	Braid TC
2713/5	5	36	25/50	.005	.127	.010	.254	.072	1.83	1000'	Braid TC
2712/2	2	34	40/50	.005	.127	.010	.254	.065	1.65	1000'	Braid TC
2712/3	3	34	40/50	.005	.127	.010	.254	.068	1.73	1000'	Braid TC
2712/4	4	34	40/50	.005	.127	.010	.254	.070	1.78	1000'	Braid TC
2712/5	5	34	40/50	.005	.127	.010	.254	.078	1.98	1000'	Braid TC
2711/2	2	32	65/50	.005	.127	.010	.254	.069	1.75	100', 1000'	Braid TC
2711/3	3	32	65/50	.005	.127	.010	.254	.072	1.83	1000'	Braid TC
2711/4	4	32	65/50	.005	.127	.010	.254	.077	1.96	1000'	Braid TC
2711/5	5	32	65/50	.005	.127	.010	.254	.083	2.11	1000'	Braid TC
2752/5	5	32	7/40*	.007	.178	.010	.254	.082	2.08	1000'	Spiral TC
2710/2	2	30	41/46	.005	.127	.010	.254	.073	1.85	100', 1000'	Braid TC
2710/3	3	30	41/46	.005	.127	.010	.254	.076	1.93	100', 1000'	Braid TC
2710/4	4	30	41/46	.005	.127	.010	.254	.082	2.08	100', 1000'	Braid TC
2710/5	5	30	41/46	.005	.127	.010	.254	.088	2.24	100', 1000'	Braid TC
2710/8	8	30	41/46	.005	.127	.010	.254	.102	2.59	100', 1000'	Braid TC



Daburn Electronics & Cable
 44 Richboynton Road
 Dover, NJ 07849

Daburn Cat. No.	No. of Cond.	AWG	Strand.	Nom. Wall		Nom. Jacket		Nom. O.D.		Standard P-U	Shield Type
				IN	MM	IN	MM	IN	MM		
2709/2	2	28	65/46	.007	.178	.012	.305	.091	2.31	100', 1000'	Braid TC
2709/3	3	28	65/46	.007	.178	.012	.305	.095	2.41	100', 1000'	Braid TC
2709/4	4	28	65/46	.007	.178	.012	.305	.103	2.62	100', 1000'	Braid TC
2709/5	5	28	65/46	.007	.178	.012	.305	.111	2.82	100', 1000'	Braid TC
2709/10	10	28	65/46	.007	.178	.020	.508	.165	4.19	500', 1000'	Braid TC
2709/15	15	28	65/46	.007	.178	.025	.635	.195	4.95	500', 1000'	Braid TC
2708/2	2	26	105/46	.008	.203	.012	.305	.105	2.67	100', 1000'	Braid TC
2708/3	3	26	105/46	.008	.203	.012	.305	.111	2.82	100', 1000'	Braid TC
2708/4	4	26	105/46	.008	.203	.012	.305	.120	3.05	100', 1000'	Braid TC
2708/5	5	26	105/46	.008	.203	.012	.305	.130	3.30	100', 1000'	Braid TC
2707/1	1	24	105/44	.010	.254	.010	.254	.074	1.88	100', 1000'	Braid TC
2707/2	2	24	105/44	.010	.254	.015	.381	.127	3.23	100', 1000'	Braid TC
2707/3	3	24	105/44	.010	.254	.015	.381	.136	3.45	100', 1000'	Braid TC
2707/4	4	24	105/44	.010	.254	.015	.381	.147	3.73	100', 1000'	Braid TC
2706/1	1	22	168/44	.010	.254	.010	.254	.081	2.06	100', 1000'	Braid TC
2706/2	2	22	168/44	.010	.254	.015	.381	.140	3.56	100', 1000'	Braid TC
2706/3	3	22	168/44	.010	.254	.020	.508	.161	4.09	100', 1000'	Braid TC
2706/4	4	22	168/44	.010	.254	.020	.508	.174	4.42	100', 1000'	Braid TC

*tinned copper on 2752/5

Color Code: 1-Black, 2- White, 3-Red, 4-Green, 5-Yellow, 6-Blue, 7-Brown, 8-Orange, 9-Gray, 10-Violet
 2709/15 has 5 inner – white, black, red, green, yellow & 10 outer – white, black, red, green, yellow, blue, brown, orange, gray, violet

Additional constructions are available. Please call or e-mail to inquire.