



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Daburn Electronics & Cable
44 Richboynton Road
Dover, NJ 07801

#2722 Plastic Kinkless Test Lead Wire – 5,000V*

Daburn's plastic kinkless test wire has high flexibility, obtained through the combination of special soft-formula PVC and high-count, extra-flexible tinned copper wire. This light weight wire has a smooth, high gloss finish; elegant in appearance, with a high resistance to abrasion.

Although designated as test lead wire, this construction is used in non-test lead applications requiring the high degree of flexibility offered by the 2722 series. The combination of performance, appearance, and economy far outweighs the modestly larger wire O.D. of the 5,000 volt* rated test lead wire.

The wire is stable from -80°C to +80°C and exceeds the requirements of MIL-I-3930A, Type JP (PVC). It is resistant to chemical corrosion, and fungus. 5,000V* rated test lead wire.

Description: One conductor stranded tinned copper, with a special formulation vinyl insulation for a bright, smooth, glossy surface.

This series is RoHS compliant.

| DABURN Cat. No. | Size | Stranding | Wall | Nom. O.D. |
|-----------------|------|-----------|-------|-----------|
| 2722/22 | 22 | 26/36 | .032" | .100" |
| 2722/20 | 20 | 26/34 | .032" | .104" |
| 2722/18 | 18 | 65/36 | .032" | .112" |
| 2722/16 | 16 | 65/34 | .032" | .129" |

Standard Put-Ups: 100 FT, 500 FT, 1,000 FT

Stock Colors: Black, Red, Yellow, Green. White, Blue. Additional colors available to order.

Operating Temperature: -80°C to +80°C

* For intermittent duty