



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Precision ESD Safe Dissipative Drivers

Wiha Precision ESD Static Dissipative Screwdrivers meet the requirements for tools used in static sensitive areas.



Rotating cap for precise turning & control with fingertip

Molded Precision handle of impact resistant dissipative material

Tapered handle allows rapid rotation

Blade, CVM steel, hardened, hard chrome finish

Tip, precision ground for exact fit, Wiha Chromtop finish

ESD Standard IEC 61340-5-1

Surface resistance of handles is 10⁶ - 10⁹ Ohms



272 **Slotted Screwdriver, With Precision ESD Safe Dissipative Handle.** Blade high alloy chrome-vanadium-molybdenum steel. Hard chrome finished. Handle manufactured from impact resistant, dissipative material. ESD standard IEC 61340-5-1

Item No.	mm	Inch	mm	Inch	mm	Inch	mm	Inch	lbs.	pkg.
272 08	.8	1/32	40	1.6	0.16	.01	120	4.7	.02	10
272 10	1.0	.039	40	1.6	0.18	.01	120	4.7	.02	10
272 12	1.2	3/64	40	1.6	0.20	.01	120	4.7	.02	10
272 15	1.5	1/16	40	1.6	0.25	.01	120	4.7	.02	10
272 20	2.0	5/64	40	1.6	0.40	.02	120	4.7	.02	10
272 22	2.0	5/64	75	3.0	0.40	.02	155	6.1	.03	10
272 23	2.0	5/64	100	3.9	0.40	.02	180	7.1	.03	10
272 24	2.0	5/64	150	5.9	0.40	.02	260	10.2	.04	10
272 25	2.5	3/32	50	2.0	0.40	.02	145	5.7	.04	10
272 27	2.5	3/32	100	3.9	0.40	.02	195	7.7	.03	10
272 28	2.5	3/32	150	5.9	0.40	.02	245	9.6	.04	10
272 30	3.0	1/8	50	2.0	0.50	.02	145	5.7	.04	10
272 32	3.0	1/8	100	3.9	0.50	.02	210	8.3	.04	10
272 34	3.0	1/8	150	5.9	0.50	.02	260	10.2	.05	10
272 35	3.5	9/64	60	2.4	0.60	.02	170	6.7	.06	10
272 37	3.5	9/64	100	3.9	0.60	.02	210	8.3	.06	10
272 38	3.5	9/64	150	5.9	0.60	.02	260	10.2	.06	10
272 40	4.0	5/32	60	2.4	0.80	.03	170	6.7	.06	10
272 42	4.0	5/32	100	3.9	0.80	.03	210	8.3	.06	10
272 43	4.0	5/32	150	5.9	0.80	.03	260	10.2	.07	10

*Metric dimensions actual - Inch dimensions approximate



272 90 **Set 8 Pcs. Slotted Precision ESD Safe Dissipative Handle**

Blade CVM steel, hardened, hard chromed. Handle impact resistant, dissipative material. In storage pouch. ESD standard IEC 61340-5-1

Item No.	mm	mm	mm	mm	lbs.	
272 90	272 08	.8	40	272 20	2.0 40	.54
	272 10	1.0	40	272 25	2.5 50	
	272 12	1.2	40	272 30	3.0 50	
	272 15	1.5	40	272 35	3.5 60	



273 90 **Set 7 Pcs. Slotted & Phillips Precision ESD Safe Dissipative Handle.**

Blade high alloy CVM steel, hardened, hard chromed. Handle manufactured from impact resistant, dissipative material. ESD standard IEC 61340-5-1

Item No.	mm	mm	Size	mm	lbs.	
273 90	272 15	1.5	40	273 05	00 40	.30
	272 20	2.0	40	273 10	0 50	
	272 25	2.5	50	273 20	1 60	
	272 35	3.5	60			