



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Termination board - IBS PCI SC/RI/I-T - 2730080

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Termination board - system coupler with copper connection

### Product description

INTERBUS system coupler for PCs with PCI bus

System couplers integrate master and slave functions in one controller board at reduced space and low cost.

They can be used wherever the PC takes over control functions in a lower-level INTERBUS system and at the same time requires a non-interacting link to a higher-level INTERBUS system.

A typical example is the internal control of a robot with a PC and the simultaneous link to the system network.

The software interfaces to the application program are compatible with the INTERBUS Generation 4 PC controller boards, such as the IBS PCI SC/I-T.

As with all Generation 4 boards, configuration, parameterization and diagnostics are supported by the INTERBUS CMD software.

The system coupler allows for the connection of an external 24 V DC power supply to ensure uninterrupted operation of the higher-level INTERBUS system.

### Product Features

- External 24 V DC power supply
- Direct integration into OPC-based visualization systems via OPC server
- Installation of several cards in a PC with monitoring of multiple INTERBUS lines
- Parameterization and diagnostics with Diag+
- Compatible driver
- Access to INTERBUS system data and controller data via visualization stations
- INTERBUS parameter channel (PCP) supported
- Access to high-level language applications via HFI



### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	363.7 GRM
Custom tariff number	84733020
Country of origin	Germany

# Termination board - IBS PCI SC/RI/I-T - 2730080

## Technical data

### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

### Ambient conditions

Degree of protection	IP00
----------------------	------

### Control system

Control system	PCI bus
Diagnostics tool	DIAG+ from version 1.14
Configuration tool	CMD from version 4.5x

### Software interfaces

Software driver	Windows NT
	Windows 2000
	Windows XP
	Windows 7
	Venturcom RTX 5.x
	Further types on request
Application interface	HLI
	OPC
	DDI

### Software requirements

Configuration tool	CMD from version 4.5x
	Config+ from version 1.00 onwards
Diagnostics tool	DIAG+ from version 1.14

### Power supply

Power supply connection	Via PCI bus (master) and 2-pos. MINI COMBICON (slave part)
Typical current consumption	0.8 A
Supply voltage	5 V DC
	24 V DC (external, environment class 1)
Supply voltage range	18.5 V DC ... 30.2 V DC (including ripple (0.5 Vpp))

### General

Weight	280 g
Format	176 x 107 mm (IBS PCI SC/RI/LK: 168 x 107 mm)

### Data interfaces

Interface	INTERBUS remote bus
-----------	---------------------

# Termination board - IBS PCI SC/RI/I-T - 2730080

## Technical data

### Data interfaces

Connection method	9-pos. D-SUB female connector (optionally optical fiber possible via interface converters) with electrical isolation
Interface	Parameterization/operation/diagnostics
Connection method	RS-232-C, Mini-DIN female
Interface	Host system
Connection method	IBM-compatible PCI slot in acc. with PCI specification 2.1 or higher, PCI bus, 32 bit, 33 MHz, 5 V
Interrupts	1 IRQ, PNP

### Fieldbus function

Amount of process data	max. 8192 Bit (INTERBUS-Master)
	256 Bit (INTERBUS-Slave)
Number of supported devices	max. 512 (in total, of which 254 are remote bus devices/bus segments)
Number of devices with parameter channel	max. 126
Module classification	INTERBUS master/slave

## Classifications

### eCl@ss

eCl@ss 4.0	27240603
eCl@ss 4.1	27240603
eCl@ss 5.0	27242208
eCl@ss 5.1	27242208
eCl@ss 6.0	27242208
eCl@ss 7.0	27242208
eCl@ss 8.0	27242208

### ETIM

ETIM 2.0	EC001425
ETIM 3.0	EC001425
ETIM 4.0	EC000236

### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404



# Termination board - IBS PCI SC/RI/I-T - 2730080

## Approvals

Approvals

---

Approvals

UL Recognized / cUL Recognized / cULus Recognized

---


Ex Approvals


---

Approvals submitted

---

## Approval details

UL Recognized 

cUL Recognized 

cULus Recognized 

---