



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Distributed I/O device - IBS RL 24 DIO 8/5-RS-LK-2MBD - 2734905

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Digital I/O device for INTERBUS; fiber optic technology with 2 Mbaud, eight inputs (24 V DC), five relay outputs (12 V AC to 440 V AC; 2 A, maximum), sensor connection via 5-pos. M12 female connectors, rugged metal housing, IP67 protection

Product Features

- Rugged metal housing
- Comprehensive diagnostic functions
- Rugged Line connector for INTERBUS with fiber optic and supply voltage
- COMBICON connector for relay outputs
- M12 connector for digital inputs



Key commercial data

| | |
|--------------------------------------|------------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 4037.0 GRM |
| Custom tariff number | 85389091 |
| Country of origin | Germany |

Technical data

Note

| | |
|-------------------------|---|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---|

Dimensions

| | |
|--------------------|--|
| Width | 185 mm |
| Height | 193 mm |
| Depth | 138 mm |
| Note on dimensions | With bus connectors and mounting plate |

Ambient conditions

Distributed I/O device - IBS RL 24 DIO 8/5-RS-LK-2MBD - 2734905

Technical data

Ambient conditions

| | |
|--|--|
| Ambient temperature (operation) | 0 °C ... 55 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Permissible humidity (operation) | 100 % |
| Permissible humidity (storage/transport) | 95 % (non-condensing) |
| Air pressure (operation) | 860 hPa ... 1080 hPa (up to 1500 m above mean sea level) |
| Air pressure (storage/transport) | 660 hPa ... 1080 hPa (up to 3500 m above mean sea level) |
| Degree of protection | IP65/IP67 |

General

| | |
|------------------|---|
| Weight | 3.5 kg |
| Mounting type | Wall mounting |
| Protection class | III, IEC 61140, EN 61140, VDE 0140-1 |
| Note | Seal unused slots/connections to ensure the degree of protection. |
| Test section | Between US1 and US2 500 V AC 50 Hz 1 min |
| | Between US1 and functional earth ground 500 V AC 50 Hz 1 min |
| | Between US2 and functional earth ground 500 V AC 50 Hz 1 min |
| | Between US1 and relay contacts 2.5 kV 50 Hz 1 min |
| | Between US2 and relay contacts 2.5 kV 50 Hz 1 min |
| | Between relay contacts and functional earth ground 2.5 kV 50 Hz 1 min |

Interfaces

| | |
|----------------------|---|
| Fieldbus system | INTERBUS |
| Designation | INTERBUS |
| Connection method | Optic fiber (polymer fiber 980/1000 µm) |
| Transmission speed | 2 MBit/s |
| Transmission physics | FO |

Power supply for module electronics

| | |
|-------------------------------------|--|
| Supply voltage | 24 V DC |
| Supply voltage range | 18.5 V DC ... 32 V DC (including ripple) |
| Ripple | Max 3.6 V _{SS} within the permissible voltage range |
| Supply current | typ. 120 mA (plus sensor current) |
| Communications power U _L | 24 V DC |
| Current consumption | 80 mA (plus sensor current) |

Digital inputs

| | |
|--------------------------|------------------------------------|
| Input name | Digital inputs |
| Description of the input | Voltage input 230 V AC to 400 V AC |
| Connection method | 2, 3, 4-wire |

Distributed I/O device - IBS RL 24 DIO 8/5-RS-LK-2MBD - 2734905

Technical data

Digital inputs

| | |
|------------------------------------|--|
| Number of inputs | 8 |
| Protective circuit | Electronic short-circuit/overload protection |
| Input voltage | 24 V |
| Input voltage range "0" signal | -30 V ... 5 V |
| Input voltage range "1" signal | 15 V ... 32 V |
| Delay at signal change from 0 to 1 | 2.2 ms |
| Delay at signal change from 1 to 0 | 3.3 ms |

Digital outputs

| | |
|------------------------------------|--------------|
| Output name | Relay output |
| Number of outputs | 5 |
| Maximum output current per channel | 2 A |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27250304 |
| eCl@ss 4.1 | 27250304 |
| eCl@ss 5.0 | 27250304 |
| eCl@ss 5.1 | 27242604 |
| eCl@ss 6.0 | 27242605 |
| eCl@ss 7.0 | 27242605 |
| eCl@ss 8.0 | 27242604 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001433 |
| ETIM 3.0 | EC001601 |
| ETIM 4.0 | EC001601 |
| ETIM 5.0 | EC001601 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11 | 43172015 |
| UNSPSC 12.01 | 43201404 |
| UNSPSC 13.2 | 43201404 |

Distributed I/O device - IBS RL 24 DIO 8/5-RS-LK-2MBD - 2734905

Approvals

Approvals

Approvals

INTERBUS CLUB

Ex Approvals

Approvals submitted

Approval details

| |
|---------------|
| INTERBUS CLUB |
|---------------|
