



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Electronics & Cable

44 Richboynton Road, Dover, NJ 07801

973 328 3200 F. 973 328 3130

#2754 - #2764 Plastic Speaker Cable - Clear And Colored Insulation

Plastic Speaker Cable

Clear And Colored Insulation

Description: Conductors are parallel, stranded copper, color coded and clear polyvinylchloride insulation. Polarity is determined by TC/BC or by identification on one leg. Conductors separate quickly when split apart. Suitable for HI-FI speaker cable, miniature juke-box speaker connections, rear audio speaker extension cable. Clear insulation blends with any interior.

Temperature Rating: -20°C To + 60°C.

Operating Voltage: 300V.

DABURN Cat. No.	No. Of Cond.	Cond. Size	Cond. Strand	Nom. Wall		Nom. OD		Stock Colors	Standard Packaging
				IN.	MM.	IN.	MM.		
2754	2	24	7/32	0.016	0.41	.057 x .120	1.45 x 3.05	BN/BK/WH/GR/TN	100', 500', 1000'
2755	2*	24	7/32	0.016	0.41	.057 x .120	1.45 x 3.05	Clear	100', 500', 1000'
2753	2	22	7/30	0.020	0.51	.070 x .140	1.78 x 3.56	Clear	100', 500', 1000'
2756	2	20	10/30	0.016	0.41	.085 x .175	2.16x 4.45	BN/BK/WH/GY/TN	100', 500', 1000'
2757	2*	20	10/30	0.016	0.41	.085 x .175	2.16x4.45	Clear	100', 500', 1000'
2758	2	18	41/34	0.032	0.81	.115 x .215	2.92 x 5.46	BN/BK/WH/GY/TN	100', 500', 1000'

2759	2	18	41/34	0.032	0.81	.115 x .215	2.92 x 5.46	Clear	100', 500', 1000'	
2760	2*	16	26/30	0.030	0.76	.115 x .215	2.92 x 5.46	Clear	100', 500', 1000'	
2761	2*	14	41/30	0.030	0.76	.140 x .290	3.56 x 7.37	Clear	100', 500', 1000'	
2765	2**	14	168/36	0.055	1.40	.200 x .415	5.08 x 10.54	Clear	100', 500', 1000'	
2766	2**	16	105/36	0.055	1.40	.160 x .355	4.06x8.51	Clear	100', 500', 1000'	
2762	2**	12	259/36	0.055	1.40	.200 x .415	5.08 x 10.54	Clear	100', 500', 1000'	
2763	2**	10	413/36	0.055	1.40	.240 x .485	6.10 x 12.32	Clear	100', 500', 1000'	
2764	2**	8	665/36	0.055	1.40	.250 x .500	6.35 x 12.70	Clear	100', 500', 1000'	

* 1 conductor tinned copper, 1 conductor bare copper.

** Extra flexible stranding.

Put-Ups: 100', 500', 1000'.

Additional Put-Ups and colors available.