



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Wiha Precision ESD Safe Nut Drivers



SHOP



ESD standard
IEC 61340-5-1



SHOP

277 Inch Nut Driver, With Precision ESD Safe Dissipative

Handle. Blade high alloy chrome-vanadium-molybdenum steel. Hard chrome finished. Handle manufactured from impact resistant, dissipative material. ESD standard IEC 61340-5-1

Item									
No.	Inch	mm	Inch	mm	Inch	Inch	Inch	lbs.	pkg.
277 01	3/32	60	2.4	155	6.1	.16	.16	.04	10
277 03	7/64	60	2.4	155	6.1	.20	.20	.05	10
277 05	1/8	60	2.4	155	6.1	.20	.20	.05	10
277 07	9/64	60	2.4	155	6.1	.21	.24	.05	10
277 09	5/32	60	2.4	155	6.1	.22	.24	.05	10
277 11	3/16	60	2.4	155	6.1	.25	.28	.05	10
277 13	7/32	60	2.4	170	6.7	.30	.32	.06	10
277 15	1/4	60	2.4	170	6.7	.34	.36	.06	10

*Metric dimensions actual - Inch dimensions approximate

277 91 Set 8 Pcs. Inch Nut Driver Precision ESD Safe Dissipative

Handle Blade CVM steel, hardened, hard chromed. Handle impact resistant, dissipative material. In storage pouch

Item						
No.	Inch	mm	Inch	mm	lbs.	
277 91	277 01	3/32	60	277 09	5/32	60
	277 03	7/64	60	277 11	3/16	60
	277 05	1/8	60	277 13	7/32	60
	277 07	9/64	60	277 15	1/4	60



SHOP



ESD standard
IEC 61340-5-1



SHOP

277 Metric Nut Driver, With Precision ESD Safe Dissipative

Handle. Blade high alloy chrome-vanadium-molybdenum steel. Hard chromed finished. Handle manufactured from impact resistant, dissipative material. ESD standard IEC 61340-5-1

Item									
No.	mm	mm	Inch	mm	Inch	Inch	Inch	lbs.	pkg.
277 20	1.5	60	2.4	140	5.5	2.5	3.0	.03	10
277 22	2.0	60	2.4	140	5.5	3.2	4.0	.04	10
277 25	2.5	60	2.4	140	5.5	4.0	4.0	.05	10
277 30	3.0	60	2.4	155	6.1	5.0	5.0	.06	10
277 35	3.5	60	2.4	155	6.1	5.3	6.0	.06	10
277 40	4.0	60	2.4	155	6.1	5.5	6.0	.06	10
277 45	4.5	60	2.4	155	6.1	6.2	7.0	.05	10
277 50	5.0	60	2.4	155	6.1	6.8	7.0	.06	10
277 55	5.5	60	2.4	170	6.7	7.6	8.0	.07	10
277 60	6.0	60	2.4	170	6.7	9.6	10.0	.06	10

*Metric dimensions actual - Inch dimensions approximate

277 90 Set 8 Pcs. Metric Nut Driver Precision ESD Safe

Dissipative Handle Blade CVM steel, hardened, hard chromed. Handle impact resistant, dissipative material. In storage pouch

Item						
No.	mm	mm	mm	mm	lbs.	
277 90	277 20	1.5	60	277 35	3.5	60
	277 22	2.0	60	277 40	4.0	60
	277 25	2.5	60	277 50	5.0	60
	277 30	3.0	60	277 55	5.5	60