



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Distributed I/O device - FLX ASI DIO 2/2 M12-2A - 2773432

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



AS-i digital input/output module, AB slave, 2 digital inputs, 24 V DC, 2, 3 and 4-conductor connection method, 2 digital outputs, 24 V DC, IP67 protection

Product description

The digital Fieldline M12 AS-Interface input/output modules with IP67 housing protection make it possible to connect digital sensors and actuators to the AS-i using M12 plugs using the SPEEDCON connection method.

The modules are connected to AS-i using the flat-ribbon cable cable penetration technique.

Product Features

- ✓ Tool-free connection to AS-Interface using penetration technique
- ✓ M12 connection technology with SPEEDCON fast locking system for the I/Os
- ✓ Optimized for direct mounting and DIN rail mounting



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	226.6 GRM
Custom tariff number	85176200
Country of origin	Singapore

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	58 mm
Height	118 mm
Depth	35 mm
Drill hole spacing	108 mm

Distributed I/O device - FLX ASI DIO 2/2 M12-2A - 2773432

Technical data

Ambient conditions

Ambient temperature (operation)	-25 °C ... 70 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Degree of protection	IP65/IP67

Interfaces

Fieldbus system	AS-i
Designation	AS-Interface
Connection method	Flat-ribbon cable penetration technique
Designation connection point	AS-i
Transmission speed	167 kBit/s
Number of positions	4

AS-Interface

Slave type	A/B slave
AS-i specification	2.1
IO code	B
ID1 code	7
ID2 code	2
ID code (hex)	A
ID code (dec.)	10
AS-i profile	S-B.A.2
Required master specification	>= 2.0

Digital inputs

Input name	Digital inputs
Connection method	M12 connector
	2, 3-wire
Number of inputs	2
Input characteristic curve	IEC 61131-2 type 2

Digital outputs

Output name	Digital outputs
Connection method	M12 connector
	2-wire
Number of outputs	2
Maximum output current per channel	2 A
Maximum output current per module / terminal block	4 A

General

Weight	195 g
--------	-------

Distributed I/O device - FLX ASI DIO 2/2 M12-2A - 2773432

Technical data

General

Mounting type	Wall mounting
Protection class	III, IEC 61140, EN 61140, VDE 0140-1

Classifications

eCl@ss

eCl@ss 4.0	27250302
eCl@ss 4.1	27250302
eCl@ss 5.0	27250302
eCl@ss 5.1	27242604
eCl@ss 6.0	27242604
eCl@ss 7.0	27242604
eCl@ss 8.0	27242604

ETIM

ETIM 2.0	EC001430
ETIM 3.0	EC001599
ETIM 4.0	EC001599
ETIM 5.0	EC001599

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Approvals

Approvals

Approvals

UL Listed / cUL Listed / ASI-Interface / cULus Listed

Ex Approvals

Distributed I/O device - FLX ASI DIO 2/2 M12-2A - 2773432

Approvals

Approvals submitted

Approval details

- UL Listed
- cUL Listed
- ASI-Interface
- cULus Listed

Drawings

Connection diagram

