



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



UFBK-BE


Discontinued item

Order No.: 2783095

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2783095>

Base element with inductive decoupling for protective plug UFBK and UFBK-M, with universal foot for mounting on NS 32 or NS 35/7.5, housing width: 17.5 mm

Commercial data

GTIN (EAN)	 4 017918 069810
Note	Made-to-order
sales group	J223
Pack	10 pcs.
Customs tariff	85363010

Product notes

WEEE/RoHS-compliant since:
02/14/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

Nominal current I _N	2 A
Ambient temperature (operation)	-40 °C ... 80 °C
Inflammability class acc. to UL 94	V2
Degree of protection	IP20
Pitch unit	1 Div.

Certificates / Approvals



Certification

GOST

Accessories

Item	Designation	Description
Plug/Adapter		
2781576	CS-UFBK	Keying pins for later keying of the base elements without keying belonging to the PLUGTRAB UFBK and UAK product ranges.

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;