



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Surge protection device - TT-UKK5-M/ 24DC - 2795960

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Double-level modular terminal block with suppressor diode as surge protection between both levels, disconnect knife in the upper level, nominal voltage: 24 V DC, for mounting on NS 32 or NS 35/7.5, closed housing, terminal width: 6.2 mm, terminal height: 68 mm

### Why buy this product

- Can be used in the signal circuits of electronic controllers



### Key commercial data

Packing unit	1
Minimum order quantity	50
Catalog page	Page 111 (TT-2011)
GTIN	 4 017918 073220
Custom tariff number	85363010
Country of origin	GREECE

### Technical data

#### General

Housing material	PA
Inflammability class according to UL 94	V2
Color	black
Standards for air and creepage distances	VDE 0110-1
Total surge current (8/20) $\mu$ s	169 A
Ambient temperature (operation)	-40 °C ... 85 °C
Mounting type	DIN rail/G-profile rail
Design	Double-level terminal block with disconnect knife
Number of positions	1
Degree of protection	IP20
Direction of action	Line-Line
Width	6.2 mm
Height	68 mm
Length	80 mm

# Surge protection device - TT-UKK5-M/ 24DC - 2795960

## Technical data

### Protective circuit

IEC category	C3
VDE requirement class	C3
Nominal voltage UN	24 V DC
Maximum continuous operating voltage UC	28 V DC
Maximum continuous operating voltage UC	20 V AC
Maximum continuous voltage UC (wire-wire)	28 V DC
Maximum continuous voltage UC (wire-ground)	20 V AC
Nominal current IN	12 A (45°C)
Operating effective current IC at UC	≤ 5 μA
Nominal discharge surge current In (8/20) μs (Core-Core)	169 A
Total surge current (8/20) μs	169 A
Max. discharge surge current I <sub>max</sub> (8/20) μs maximum (Core-Core)	169 A
Nominal pulse current I <sub>an</sub> (10/1000) μs (Core-Core)	33 A
Output voltage limitation at 1 kV/μs (Core-Core) static	≤ 40 V
Residual voltage at I <sub>n</sub> , (conductor-conductor)	≤ 55 V
Response time t <sub>A</sub> (Core-Core)	≤ 1 ns
Cut-off frequency f <sub>g</sub> (3 dB), sym. in 150 Ohm system	Typ. 1.2 MHz
Capacity (Core-Core)	≤ 1.6 nF
Surge carrying capacity in acc. with IEC 61643-21 (Core-Core)	C3 (25 A)

### Connection data

Connection method	Screw connection
Connection type IN	Screw terminal blocks
Connection type OUT	Screw terminal blocks
Screw thread	M3
Tightening torque	0.5 Nm
Stripping length	8 mm
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	4 mm <sup>2</sup>
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

### Connection, protective circuit

Standards/regulations	IEC 61643-21
-----------------------	--------------

## Classifications

### eClass

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801

# Surge protection device - TT-UKK5-M/ 24DC - 2795960

## Classifications

### eclass

eCl@ss 5.1	27130801
eCl@ss 6.0	27130807
eCl@ss 7.0	27130807

### etim

ETIM 2.0	EC000943
ETIM 3.0	EC000943
ETIM 4.0	EC000943

### unspsc

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

## Approvals

### Approvals

Approvals

CSA / GOST / GOST

Ex Approvals

Approvals submitted

### Approval details


mm <sup>2</sup> /AWG/kcmil	24-12
Nominal current I <sub>N</sub>	12 A
Nominal voltage U <sub>N</sub>	24 V

--	--




# Surge protection device - TT-UKK5-M/ 24DC - 2795960

## Approvals



## Drawings

### Circuit diagram



### Schematic diagram

