



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



FO cable - PSM-LWL-GDM-RUGGED- 50/125 - 2799322

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fiberglass cable, duplex 50/125 µm, by the meter, without connector, for indoor installation

The illustration shows version PSM-LWL-HCS-200/230

Product Features

- ✓ Highly tear-resistant aramid strain relief elements
- ✓ Rugged installation cable for indoor use
- ✓ Rugged polyurethane (PUR) outer sheath
- ✓ 2.9 mm individual wires made from highly flexible FRNC material
- ✓ Halogen-free, ozone, and UV resistant

Key commercial data

Packing unit	1 M
Weight per Piece (excluding packing)	51.88 GRM
Custom tariff number	85447000
Country of origin	Germany

Technical data

Mechanical characteristics

Number of positions	2
Fiber	Fiberglass, 50/125 µm
Cable diameter	8 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Altitude	5000 m
Degree of protection	IP20

Material data

Outer sheath, material	PUR
------------------------	-----

FO cable - PSM-LWL-GDM-RUGGED- 50/125 - 2799322

Technical data

Material data

External sheath, color	orange
------------------------	--------

Electrical characteristics

Number of positions	2
---------------------	---

Line characteristics

Cable type	Multimode fiberglass
Cable abbreviation	I-V(ZN)H11Y 2G50/125 2,5B600+0,7F1200
Length of cable	Free input (1.0 ... 2000 m)
External cable diameter	8 mm
Wire colors	Red/Green
External sheath, color	orange
Cable, attenuation	2.5 dB/km (at 850 nm), 0.7 dB/km (at 1300 nm)
Outer sheath, material	PUR
Cable weight	50 kg/km
Bending radius, single element	30 mm (Short-term)
	50 mm (Permanent)
Bending radius, entire cable	65 mm (Short-term)
	65 mm (Permanent)
Tensile strength short-term/long-term	1000 N / 200 N
Lateral pressure short term	400 N/cm
Lateral pressure, long-term	100 N/cm
Impact strength	2 Nm / 10 x
cable layer type	Indoors
Halogen-free	According to IEC 60754-2

Ambient conditions

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Altitude	5000 m
Degree of protection	IP20

Classifications

eCl@ss

eCl@ss 4.0	27061001
eCl@ss 4.1	27061001
eCl@ss 5.0	27061803
eCl@ss 5.1	27061803

FO cable - PSM-LWL-GDM-RUGGED- 50/125 - 2799322

Classifications

eCl@ss

eCl@ss 6.0	27061803
eCl@ss 7.0	27061803
eCl@ss 8.0	27061803

ETIM

ETIM 2.0	EC001122
ETIM 3.0	EC001122
ETIM 4.0	EC001122
ETIM 5.0	EC000830

UNSPSC

UNSPSC 6.01	26121607
UNSPSC 7.0901	26121607
UNSPSC 11	26121607
UNSPSC 12.01	26121607
UNSPSC 13.2	26121607