



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Surge protection base element - VAL-MS BE-AR/FM - 2801066

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Base element for Type 1 and Type 2 surge arresters of the VAL-MS series, with separate field and house termination, tool-free isolation disconnect, test point, and remote indication contacts. Design: 1-channel, bridgeable.

Product Features

- Versions with and without floating remote indication contact
- Separate field and house wire termination.
- Tool-free field wire disconnect and test point.
- IP20 touch safe when connected.
- Coding when protective plug is inserted for the first time



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	148.0 GRM
Custom tariff number	85363010
Country of origin	United States

Technical data

Dimensions

Height	160 mm
Width	17.7 mm
Depth	75 mm

Ambient conditions

Degree of protection	IP20
	IP20 (when disconnect closed)
Ambient temperature (operation)	-40 °C ... 80 °C
Altitude	max. 3000 m
Permissible humidity (operation)	5 % ... 95 %

Surge protection base element - VAL-MS BE-AR/FM - 2801066

Technical data

Ambient conditions

Permissible humidity (storage/transport)	5 % ... 95 %
Shock (operation)	10g
Vibration (operation)	2g (0 ... 200 Hz)

General

Housing material	PA
Inflammability class according to UL 94	V0
Color	black
Total surge current (8/20) μ s	100 kA
Total surge current (10/350) μ s	15 kA
Mounting type	DIN rail mounting with additional retaining screw
Type	DIN rail module, two-section, divisible
Number of positions	1
Surge protection fault message	Remote indicator contact

Protective circuit

Nominal voltage U_N	500 V AC
Nominal frequency f_N	50 Hz (60 Hz)
Rated load current I_L	55 A (with 6 AWG)
Recommended backup fuse maximum	125 A (gL / gG)
Short-circuit resistance I_P with max. backup fuse (effective)	25 kA

Connection, protective circuit

Connection type IN	Screw terminal blocks
Connection type OUT	Screw terminal blocks
Screw thread	M5
Tightening torque	4.5 Nm
Stripping length	16 mm
Conductor cross section stranded min.	1.5 mm ²
Conductor cross section stranded max.	25 mm ²
Conductor cross section solid min.	1.5 mm ²
Conductor cross section solid max.	35 mm ²
Conductor cross section AWG/kcmil min.	15
Conductor cross section AWG/kcmil max	2
AWG conductor cross section	10 ... 2 (UL)

Remote indicator contact

Connection name	Remote fault indicator contact
Switching function	PDT, 1-pos.

Surge protection base element - VAL-MS BE-AR/FM - 2801066

Technical data

Remote indicator contact

Connection method	Screw connection
Screw thread	M2
Tightening torque	0.25 Nm
	2 lb _f -in. ... 4 lb _f -in. (UL)
Stripping length	7 mm
Conductor cross section stranded min.	0.14 mm ²
Conductor cross section stranded max.	1.5 mm ²
Conductor cross section solid min.	0.14 mm ²
Conductor cross section solid max.	1.5 mm ²
Conductor cross section AWG/kcmil min.	28
Conductor cross section AWG/kcmil max	16
Maximum operating voltage U _{max} AC	250 V AC
Max. operating current I _{max}	1 A AC (250 V AC)
	1 A DC (30 V DC)

NEMA / UL data

Maximum Surge Current per Phase	100 kA
---------------------------------	--------

Classifications

eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130802
eCl@ss 7.0	27130802
eCl@ss 8.0	27130802

ETIM

ETIM 3.0	EC000941
ETIM 4.0	EC000381
ETIM 5.0	EC000381

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610

Surge protection base element - VAL-MS BE-AR/FM - 2801066


Classifications

UNSPSC

UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Drawings

Circuit diagram



Dimensioned drawing

