



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Surge protection device - TT-EX(I)- 24DC - 2832124

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Modular terminal block with three-stage surge protection for a floating Ex-i signal circuit, separate PE connection, nominal voltage: 24 V DC, for mounting on NS 35/7.5, terminal block width: 6.2 mm, terminal block height: 54.6 mm. HART-compatible

### Why buy this product

- Versions with and without disconnect knife
- To terminate a row of TERMITRAB TT... devices, covers are available in the corresponding colors
- Other voltage levels available on request
- Protection of a floating double wire in intrinsically safe circuits
- Multi-stage modular terminal blocks with screw connection technology
- Disconnection of signal circuits by disconnect knife



### Key Commercial Data

Packing unit	10 STK
GTIN	
GTIN	4017918172831

### Technical data

#### Dimensions

Height	79.6 mm
Width	6.2 mm
Depth	54.6 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
Altitude	≤ 2000 m (amsl (above mean sea level))
Degree of protection	IP20 (with end cover)

#### General

# Surge protection device - TT-EX(I)- 24DC - 2832124

## Technical data

### General

Housing material	PA 6.6
Flammability rating according to UL 94	V-0
Color	sky blue RAL 5015
Standards for clearances and creepage distances	EN 60079-11
Mounting type	DIN rail: 35 mm
Type	Double-level terminal block with PE foot – separate PE connection
Direction of action	Line-Line & Line-Earth Ground

### Protective circuit

IEC test classification	C1
	C2
	C3
	D1
Nominal voltage $U_N$	24 V DC
Maximum continuous voltage $U_C$	30 V DC
	21 V AC
Rated current	250 mA (40 °C)
Operating effective current $I_C$ at $U_C$	$\leq 5 \mu A$
Residual current $I_{PE}$	$\leq 1 \mu A$
Nominal discharge current $I_n$ (8/20) $\mu s$ (line-line)	5 kA
Nominal discharge current $I_n$ (8/20) $\mu s$ (line-earth)	5 kA
Pulse discharge current $I_{imp}$ (10/350) $\mu s$ (line-earth)	500 A
Total discharge current $I_{total}$ (8/20) $\mu s$	10 kA
Nominal pulse current $I_{an}$ (10/1000) $\mu s$ (line-line)	100 A
Nominal pulse current $I_{an}$ (10/1000) $\mu s$ (line-earth)	100 A
Output voltage limitation at 1 kV/ $\mu s$ (line-line) spike	$\leq 50 V$
Output voltage limitation at 1 kV/ $\mu s$ (line-earth) spike	$\leq 1.7 kV$
Output voltage limitation at 1 kV/ $\mu s$ (line-line) static	$\leq 50 V$
Output voltage limitation at 1 kV/ $\mu s$ (line-earth) static	$\leq 1.7 kV$
Voltage protection level $U_p$ (line-line)	$\leq 55 V$ (C1 - 1 kV/500 A)
	$\leq 75 V$ (C2 - 10 kV / 5 kA)
	$\leq 50 V$ (C3 - 10 A)
	$\leq 50 V$ (C3 - 100 A)
Voltage protection level $U_p$ (line-earth)	$\leq 2.2 kV$ (C2 - 10 kV / 5 kA)
	$\leq 1.5 kV$ (C3 - 10 A)
	$\leq 2 kV$ (C3 - 100 A)
	$\leq 2 kV$ (D1 - 500 A)
Response time $t_A$ (line-line)	$\leq 1 ns$
Response time $t_A$ (line-earth)	$\leq 100 ns$
Input attenuation aE, sym.	typ. 0.7 dB ( $\leq 400 kHz/50 \Omega$ )
	typ. 0.3 dB ( $\leq 200 kHz / 150 \Omega$ )

# Surge protection device - TT-EX(I)- 24DC - 2832124

## Technical data

### Protective circuit

Cut-off frequency $f_g$ (3 dB), sym. in 50 Ohm system	typ. 6 MHz
Cut-off frequency $f_g$ (3 dB), sym. in 150 Ohm system	typ. 2 MHz
Capacity (line-line)	$\leq 2$ nF
Resistance in series	$4.7 \Omega \pm 20 \%$
Surge protection fault message	none
Max. required back-up fuse	250 mA (T)
Impulse durability (line-line)	C1 - 1 kV/500 A
	C2 - 10 kV/5 kA
	C3 - 100 A
Impulse durability (line-earth)	C2 - 10 kV/5 kA
	C3 - 100 A
	D1 - 500 A
Alternating current carrying capacity (line-earth)	0.5 A - 1 s

### Connection data

Connection method	Screw terminal blocks
Screw thread	M3
Tightening torque	0.6 Nm
Stripping length	8 mm
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section solid	0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>
Conductor cross section AWG	24 ... 14

### Standards and Regulations

Standards/specifications	EN 61643-21 2001 + A1:2009 + A2:2013
	EN 60079-0 2012
	EN 60079-11 2012
	EN 60079-26 2007
	IEC 60079-0 2011
	IEC 60079-11 2011
	IEC 60079-26 2006

### General

Maximum inner capacitance $C_i$	2 nF
Max. internal inductance $L_i$	1 $\mu$ H
Maximum inner time factor ( $R_i/L_i$ )	0.1 $\mu$ s
Max. input current $I_i$	250 mA ( $T_A < 40$ °C)
Max. input voltage $U_i$	30 V DC
max. input power $P_i$	0.75 W
Ambient temperature (operation)	-40 °C ... 40 °C (T6 / 85 °C)
	-40 °C ... 50 °C (T5 / T 100 °C)
	-40 °C ... 80 °C (T4 / 135 °C)

# Surge protection device - TT-EX(I)- 24DC - 2832124

## Technical data

### Conformity / approvals


ATEX	# II 1G Ex ia IIC T4...T6 Ga
	# II 1D Ex ia IIIC T135°C...T85°C Da
IECEX	Ex ia IIC T4...T6 Ga
	Ex ia IIIC T135 °C...T85 °C Da

### Environmental Product Compliance


China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

## Drawings


Diagram



Dimensional drawing



Circuit diagram



## Approvals

### Approvals

Approvals

UL Listed / EAC / EAC

Ex Approvals

IECEX / ATEX / UL Listed / cUL Listed / cULus Listed

## Surge protection device - TT-EX(I)- 24DC - 2832124

### Approvals

#### Approval details

UL Listed		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 138168
-----------	---	---	---------------

EAC			EAC-Zulassung
-----	---	--	---------------

EAC			RU C- DE.A*30.B01561
-----	---	--	-------------------------

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>