



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




FL CAT5 PATCH 3,0

Order No.: 2832292

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2832292>

Patch cable, CAT5, assembled, 3.0 m

Commercial data	
GTIN (EAN)	 4 046356 044028
sales group	K009
Pack	10 pcs.
Customs tariff	85444210
Catalog page information	Page 203 (AX-2009)

Product notesWEEE/RoHS-compliant since:
11/07/2006

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
External sheath	
Outer sheath, material	LSFROH
External diameter	5.5 mm
Single wire	
Individual wires per module	8
Single wire, material	Cu litz wire

Single wire, cross section	0.14 mm ²
Mechanical properties	
Smallest bending radius, fixed installation	30 mm
Ambient temperature (operation)	-10 °C ... 60 °C
General data	
Nominal voltage U _N	150 V _{rms}

Accessories

Item	Designation	Description
General		
2891194	FL PATCH CCODE BK	Color marking for patch cable, black
2891495	FL PATCH CCODE BN	Color marking for patch cable, brown
2891291	FL PATCH CCODE BU	Color marking for patch cable, blue
2891796	FL PATCH CCODE GN	Color marking for patch cable, green
2891699	FL PATCH CCODE GY	Color marking for patch cable, gray
2891893	FL PATCH CCODE RD	Color marking for patch cable, red
2891990	FL PATCH CCODE VT	Color marking for patch cable, purple
2891592	FL PATCH CCODE YE	Color marking for patch cable, yellow
2891424	FL PATCH GUARD	Lockable security element
2891246	FL PATCH SAFE CLIP	Security element for FL patch cable

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;