



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



FL SWITCH MM HS


Order No.: 2832328



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2832328>

Modular switch system, head station, can be expanded to 24 Ethernet ports



Commercial data	
GTIN (EAN)	 4 017918 929091
Note	Made-to-order
sales group	K000
Pack	1 pcs.
Customs tariff	85176200
Catalog page information	Page 187 (AX-2009)

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Interfaces	
Interface	Ethernet
No. of ports	8 (Can be extended to a maximum of 24 ports)
Type of connection	8 ports via FL IF (interface) modules
Transmission physics	Copper
Transmission speed	10/100 MBit/s
Interface	Ethernet FO
No. of ports	8 (Can be extended to a maximum of 24 ports)

Type of connection	Via interface modules
Transmission physics	Multimode glass fiber
Transmission speed	100 MBit/s (full duplex)
Transmission length	Up to 10000 m (depending on the fiber used)
	1300 nm
Interface	Serial (V.24 (RS-232))
Type of connection	V.24 (RS-232-C), 6-pos. MINI-DIN female connector (PS/2)

Function

Basic functions	Store and forward switch complies with IEEE 802.3 2 priority classes in acc. with IEEE 802.1 P TCP/IP protocol, BootP-capable, port-mirroring, integrated web server function, multicast filtering, IGMP snooping, VLAN, Rapid Spanning Tree (RSTP), port security, PROFINET-IO-device, DHCP option 82 relay agent
Management	Integrated Management Agent, SNMP protocol (private MIB, MIB-2, RMON MIB, Bridge MIB), integrated Web server function
Supported browsers	Internet Explorer 5.5 or higher
Redundancy	Spanning Tree 802.1d, Rapid Spanning Tree 802.1w, Fast Ring Detection, Media Redundancy Protocol (MRP) as per IEC 62439
Status and diagnostic indicators	Per Ethernet 2 status LEDs: LINK and switch-over Status Activity, 100, full duplex, supply voltage U_{S1} und U_{S2} (redundant supply voltage) and FAIL, two-digit 7-segment display

Network expansion parameters

Cascading depth	Network, linear, and star structure: any
Maximum conductor length ((twisted pair)	100 m

Supply voltage

Supply voltage	24 V DC
Residual ripple	3.6 V _{PP} (within the permitted voltage range)
Supply voltage range	18.5 V DC ... 30.2 V DC
Typical current consumption	350 mA (Up to 3500 mA, depending on the configuration)
Max. current consumption	3.5 A

Mechanical tests

Type of test	Shock test in acc. with IEC 60068-2-27
Test result	Operation: 25 g, 11 ms duration, semi-sinusoidal shock impulse
Type of test	Shock test in acc. with IEC 60068-2-27
Test result	Storage/Transport: 50 g, 11 ms duration, semi-sinusoidal shock impulse
Type of test	Vibration resistance in acc. with IEC 60068-2-6

Test result	Operation/Storage/Transport: 5 g, 150 Hz, Criterion 3
Type of test	Free fall in acc. with IEC 60068-2-32
Test result	1 m

Conformity with EMC directives

Test standard	IEC 61000-4-2 (ESD)
Test result	Criterion B
Test standard	IEC 61000-4-3 (immunity to radiated interference)
Test result	Criterion A
Test standard	IEC 61000-4-4 (burst)
Test result	Criterion A
Test standard	IEC 61000-4-5 (surge)
Test result	Criterion B
Test standard	IEC 61000-4-6 (immunity to conducted interference)
Test result	Criterion A
Test standard	EN 55022 (emitted interference)
Test result	Class A

General data

Weight	1350 g
Width	214 mm
Height	95 mm
Depth	115 mm
Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 55 °C (no condensation)
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Permissible humidity (operation)	10 % ... 95 % (no condensation)
Permissible humidity (storage/transport)	10 % ... 95 % (no condensation)
Air pressure (operation)	80 kPa ... 108 kPa (2000 above sea level)
Air pressure (storage/transport)	70 kPa ... 108 kPa (3000 above sea level)
Housing material	Zinc die-cast, surface bronzed and nickel-plated
Noise emission	EN 61000-6-3/-4
Noise immunity	EN 61000-6-2:2005

Certificates / Approvals




Certification ABS, CUL, GOST, UL
 Certification Ex: CUL-EX LIS, UL-EX LIS

Accessories

Item	Designation	Description
General		
2832425	FL IF 2FX SC-D	FO media module for connecting 100Base-FX multimode glass fibers (1300 nm), connection direction downwards
2832412	FL IF 2FX SC-F	FO media module for connecting 100Base-FX multimode glass fibers (1300 nm), connection direction forwards
2832205	FL IF 2FX SM SC-D	FO interface module for connecting single mode (monomode) glass fibers (1300 nm) to the Factoryline Modular Managed Switch, output downwards
2884033	FL IF 2FX ST-D	Interface module
2832742	FL IF 2HCS 100-D	Interface module, 2 ports, 100 Mbps, full duplex, for the Modular Managed Switch System, exit downward
2832852	FL IF 2POF 10/100-D	Interface module, 2 ports, 10/100 Mbps, autonegotiation for the Modular Managed Switch System, exit downward
2891084	FL IF 2POF SCRJ-D	Interface modules, 2 ports, SCRJ for POF/HCS, diagnosis-capable
2832357	FL IF 2TX VS-RJ-D	Media module with two twisted pair ports for the modular managed switch system
2832344	FL IF 2TX VS-RJ-F	Media module with two twisted-pair ports for the modular managed switch system, output towards the front
2832483	FL IF MEM 2TX-D	Memory module, 2 port twisted pair module for saving the switch configuration
2832739	FL IF TX/HCS 100-D	Interface module, one port twisted pair, one port HCS, exit downward
2832807	FL IF TX/POF 10/100-D	Interface module, one port twisted pair, one port POF, exit downward
2832331	FL MXT	Expansion, 8 Ethernet ports

Diagrams/Drawings

Dimensioned drawing



The illustration shows the head station FL SWITCH MM HS with interface module

FL SWITCH MM HS Order No.: 2832328

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2832328>

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;