



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Wiha TorqueControl Blades - For Easy Torque, TorqueFix & TorqueVario Handles



285 Slotted Interchangeable Blades For TorqueFix & TorqueVario

Slotted tip blades on narrow 5/32 Hex shafts. High alloy chrome-vanadium-molybdenum steel, hardened, satin hard chrome finish.

Item					Max. Torque		
No.	mm	Inch	mm	lbs.	Nm	pkg.	
285 34	1.5	.059	175	.07	0.15	1	
285 35	2.0	.078	175	.07	0.4	1	
285 36	2.5	.098	175	.07	0.4	1	
285 37	3.0	.118	175	.07	0.6	1	
285 38	3.5	.139	175	.07	1.1	1	
285 39	4.0	.157	175	.07	2.5	1	



285 Phillips Interchangeable Blades For TorqueFix & TorqueVario

Phillips tip blades on narrow 5/32 Hex shafts. High alloy chrome-vanadium-molybdenum steel, hardened, satin hard chrome finish.

Item					Max. Torque		
No.	Size	mm	mm	lbs.	Nm	pkg.	
285 40	000	175	4.0	.07	0.4	1	
285 41	00	175	4.0	.07	0.4	1	
285 42	0	175	4.0	.07	0.4	1	
285 43	1	175	4.0	.07	3.8	1	



285 TORX® Interchangeable Blades For TorqueFix & TorqueVario

TORX® tip blades on narrow 5/32 Hex shafts. High alloy chrome-vanadium-molybdenum steel, hardened, satin hard chrome finish.

Item					Max. Torque		
No.	Size	mm	mm	lbs.	Nm	pkg.	
285 61	T5	175	4.0	.07	0.4	1	
285 62	T6	175	4.0	.07	0.6	1	
285 63	T7	175	4.0	.07	0.9	1	
285 64	T8	175	4.0	.07	1.3	1	
285 65	T9	175	4.0	.07	2.5	1	
285 66	T10	175	4.0	.07	3.8	1	
285 67	T15	175	4.0	.07	5.5	1	
285 68	T20	175	4.0	.07	8.0	1	
285 69	T25	175	4.0	.07	8.0	1	



285 TORX®Plus® Blades For TorqueFix & TorqueVario

TORX® Plus® tip blades on narrow 5/32 Hex shafts. High alloy chrome-vanadium-molybdenum steel, hardened, satin hard chrome finish.

Item					Max. Torque		
No.	Size	mm	mm	lbs.	Nm	pkg.	
285 71	IP5	175	4.0	.07	0.5	1	
285 72	IP6	175	4.0	.07	0.8	1	
285 73	IP7	175	4.0	.07	1.3	1	
285 74	IP8	175	4.0	.07	2.0	1	
285 75	IP9	175	4.0	.07	3.0	1	
285 76	IP10	175	4.0	.07	4.5	1	
285 77	IP15	175	4.0	.07	6.6	1	
285 78	IP20	175	4.0	.07	8.0	1	
285 79	IP25	175	4.0	.07	8.0	1	



285 Hex Metric Interchangeable Blades For TorqueFix & TorqueVario

Hex tip blades on narrow 5/32 Hex shafts. High alloy CVM steel, hardened, satin hard chrome finish.

Item					Max. Torque		
No.	mm	mm	lbs.	Nm	pkg.		
285 45	1.5	175	.07	0.9	1		
285 46	2.0	175	.07	1.8	1		
285 47	2.5	175	.07	3.8	1		
285 48	3.0	175	.07	8.0	1		
285 49	4.0	175	.07	8.0	1		



285 Hex Inch Interchangeable Blades For TorqueFix & TorqueVario

Hex tip blades on narrow 5/32 Hex shafts. High alloy CVM steel, hardened, satin hard chrome finish.

Item					Max. Torque		
No.	Inch	mm	mm	lbs.	Nm	pkg.	
285 55	.050	175	.07	.3	1		
285 56	1/16	175	.07	.5	1		
285 57	5/64	175	.07	.6	1		
285 58	3/32	175	.07	1.3	1		
285 59	7/64	175	.07	2.5	1		
285 60	1/8	175	.07	3.8	1		
285 87	9/64	175	.07	8.0	1		
285 88	5/32	175	.07	8.0	1		



285 MagicSpring TORX® Interchangeable Blades For TorqueFix & TorqueVario

blades on narrow 5/32 Hex shafts. High alloy CVM steel, hardened, satin hard chrome finish.

Item					Max. Torque		
No.	Size	mm	mm	lbs.	Nm	pkg.	
285 12	T6	175	4.0	.07	0.6	1	
285 27	T7	175	4.0	.07	0.9	1	
285 28	T8	175	4.0	.07	1.3	1	
285 29	T9	175	4.0	.07	2.5	1	
285 30	T10	175	4.0	.07	3.8	1	
285 31	T15	175	4.0	.07	5.5	1	
285 32	T20	175	4.0	.07	8.0	1	
285 33	T25	175	4.0	.07	8.0	1	



286 MagicSpring TORX®Plus® Interchangeable Blades For TorqueFix & TorqueVario

blades on narrow 5/32 Hex shafts. High alloy CVM steel, hardened, satin hard chrome finish.

Item					Max. Torque		
No.	Size	mm	mm	lbs.	Nm	pkg.	
286 11	IP6	175	4.0	.07	0.8	1	
286 12	IP7	175	4.0	.07	1.3	1	
286 13	IP8	175	4.0	.07	2.0	1	
286 14	IP9	175	4.0	.07	3.0	1	
286 16	IP10	175	4.0	.07	4.5	1	
286 17	IP15	175	4.0	.07	6.6	1	
286 18	IP20	175	4.0	.07	8.0	1	
286 19	IP25	175	4.0	.07	8.0	1	



*None of the blades featured on this page will function in a TorqueVario Insulated Handle