

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



Type 2 arrester replacement plug (surge arrester) with high-capacity varistor with low leakage current



Key commercial data

Packing unit	1
Minimum order quantity	1
Catalog page	Page 28 (TT-2011)
GTIN	4 017918 956509
Custom tariff number	85363030
Country of origin	GERMANY

Technical data

Standards

Housing material	PBT
Inflammability class according to UL 94	V0
Color	gray
Standards for air and creepage distances	DIN VDE 0110-1
Standards for air and creepage distances	IEC 60664-1
Standards for air and creepage distances	IEC 61643-1
Surge voltage category	III
Pollution degree	2
Degree of protection	IP20
Mounting type	On base element
Design	DIN rail module, two-section, divisible
Number of positions	1
Ambient temperature (operation)	-40 °C 80 °C
Message: Surge protection fault	Optical
Direction of action	L-N / L-PEN

Protective circuit

IEC category	II



Technical data

Protective circuit

T2
T2
240 V AC
350 V AC
415 V AC (5 sec.)
50 Hz
60 Hz
≤ 250 μA (ground conductor current IPE)
≤ 0.35 mW
≤ 3.5 mW
40 kA
20 kA
≤ 1.5 kV
≤ 1.4 kV (at In)
≤ 1.2 kV (at 10 kA)
≤ 1.1 kV (at 5 kA)
≤ 1 kV (at 3 kA)
≤ 1.2 kV (category C3 20 kV/10 kA)
≤ 1.1 kV (category C2 10 kV/5 kA)
≤ 1 kV (category B3/C1 6 kV/3 kA)
≤ 25 ns
315 A (gL/gG)
25 kA

Connection, protective circuit

Connection type IN	FLASHTRAB/VALVETRAB plug-in system
Connection type OUT	FLASHTRAB/VALVETRAB plug-in system

Standards

Standards/regulations	IEC 61643-1 1998
Standards/regulations	DIN EN 61643-11 2002
Standards/regulations	UL 1449
Standards/regulations	IEEE C62.1
Standards/regulations	IEEE C62.34
Standards/regulations	IEEE C62.45

Classifications

eclass

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130805



Classifications

UL Recognized **9**

ec	ass

eCl@ss 7.0	27130805	
etim		
ETIM 2.0	EC000941	
ETIM 3.0	EC000941	
ETIM 4.0	EC000941	
ETIM 5.0	EC000941	
unspsc		
UNSPSC 6.01	30212010	
UNSPSC 7.0901	39121610	
UNSPSC 11	39121610	
UNSPSC 12.01	39121610	
UNSPSC 13.2	39121620	
Approvals		
UL Recognized / KEMA-KEUR / cUL Recog	gnized / GOST / GL / IECEE CB Scheme / cULus Recognized	
Ex Approvals		
Approvals submitted		
Approval details		
		_







Approvals

ST C	
EE CB Scheme	
Lus Recognized c	

© Phoenix Contact 2012 - all rights reserved http://www.phoenixcontact.com