



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



RAD-PIG-EF316-MCX-N


Order No.: 2867681



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2867681>

Adapter cable, pigtail 50 cm MCX (male) -> N (male), insertion
attenuation 1.5 dB@2.4 GHz; impedance 50 Ω;

Commercial data

GTIN (EAN)	 4 017918 939052
sales group	H178
Pack	1 pcs.
Customs tariff	85442000
Catalog page information	Page 202 (NTK-2010)

Product notes

WEEE/RoHS-compliant since:
09/03/2007



<http://www.download.phoenixcontact.com>
Please note that the data given
here has been taken from the
online catalog. For comprehensive
information and data, please refer
to the user documentation. The
General Terms and Conditions of
Use apply to Internet downloads.

Technical data

General

Connection 1	Plug connector connection
Type of connection	Typ MCX (male)
Connection 2	Plug connector connection
Type of connection	Type N (male)
Fixed cable length	50 cm

Cable type	EF 316
Cable, attenuation	approx. 1.5 dB/m
Minimum bending radius	12.50 mm
External diameter	2.50 mm
Outer sheath, material	Radox (LSFH)
Connection name	Plug connector connection
Type of connection	Typ MCX (male)
Ambient temperature (operation)	-40 °C ... 70 °C

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;