

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China











www.wihatools.com



ESD Safe Adjustable TorqueControl Tools



285 ESD Safe TorqueVario-S, With Window Scale

EN ISO 6798, BS EN 26789, ASME B107.14M, +/- 6% Accuracy Ergonomic multi-component handle, light and compact. Handle sizes proportioned to optimize torque range. Audible and perceptible click when torque setting has been attained. With Certificate of accuracy.


Item	Range	=	•		
No.	Inch lbs. Incre	ments mm	lbs.	pkg.	
285 22*	15 - 80(in/oz) 2.5 It	nch oz 122 - 127	.33	1	
285 24	5 - 10 .2 lnc	ch lbs 122 - 127	.34	1	
285 26	7.5 - 20 .5 Inc	ch lbs 126 - 131	.42	1	

^{* +/- 10% (}This unit only)

Each TorqueVario handle has unique serial number and certificate of calibration



With Certificate of Calibration



285 91 Set 24 Pcs. ESD Safe Adjustable TorqueVario-S Bit Set

Certified to EN ISO 6798, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 21 Micro Bits, Micro Bit holder and Torque adjustment tool, packed in a compact durable storage box.

Item No.					
285 91	Slotted: 1.5, 2.0, 3.0, 4.0mm	lbs.			
	Phillips: #00, #0, #1	1.31			
	TORX ®: T6, T7, T8, T9, T10, T15				
	Hex Inch: .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32"				
	28524 Handle ESD Safe Range 5 - 10 Inch lbs.				

285 92 Set 24 Pcs. ESD Safe Adjustable TorqueVario-S Bit Set

Certified to EN ISO 6798, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 21 Micro Bits, Micro Bit holder and Torque adjustment tool, packed in a compact durable storage box.

Item No.	<u></u>
	lbs.
Phillips: #00, #0, #1	1.31
TORX ®: T6, T7, T8, T9, T10, T15	
Hex Inch: .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32"	
28526 Handle ESD Safe Range 7.5 - 20 Inch lbs.	

<u>See ESD Safe Tools</u> <u>On Pages 127-139, 163-165</u>





288 ESD Safe Slotted Interchangeable Blades For TorqueVario-S

Slotted tip blades on narrow 5/32 Hex shafts. High alloy chromevanadium-molybdenum steel, hardened, satin hard chrome finish.

Item	0	0	===	-	Max. Torque		CHOD
No.	mm	Inch	mm	lbs.	Nm	pkg.	SHUP
288 01	1.5	.059	175	.07	0.15	1	
288 03	2.0	.078	175	.07	0.4	1	
288 05	3.0	.118	175	.07	0.6	1	
288 07	3.5	.139	175	.07	1.1	1	
288 09	4.0	.157	175	.07	2.5	1	



288 ESD Safe Phillips Interchangeable Blades For TorqueVario-S

Phillips tip blades on narrow 5/32 Hex shafts. High alloy chromevanadium-molybdenum steel, hardened, satin hard chrome finish.

Item	•	===		-	Max. Torque	SHOP
No.	Size	mm	mm	lbs.	Nm	pkg.
288 10	000	175	4.0	.07	0.4	1
288 12	00	175	4.0	.07	0.4	1
288 14	0	175	4.0	.07	0.9	1
288 16	1	175	4.0	.07	3.8	1



288 ESD Safe TORX® Interchangeable Blades For TorqueVario-S

TORX° tip blades on narrow 5/32 Hex shafts. High alloy chromevanadium-molybdenum steel, hardened, hard chromed.

Item	0	==		↓	Max. Torque	- CHOD
No.	Size	mm	mm	lbs.	Nm	pkg.
288 25	T5	175	4.0	.07	0.4	1
288 26	T6	175	4.0	.07	0.6	1
288 27	T7	175	4.0	.07	0.9	1
288 28	T8	175	4.0	.07	1.3	1
288 29	T9	175	4.0	.07	2.5	1
288 30	T10	175	4.0	.07	3.8	1





With Certificate of Calibration +/- 10%



288 90 Set 24 Piece TorqueVario-S ESD Safe Micro-Bit Set

Certified to EN ISO 6798, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 21 Micro Bits, Micro Bit holder and Torque adjustment tool. Packed in a compact durable storage box.

Item No.						
288 90	Slotted: 1.5, 2.0, 3.0, 4.0mm Phillips: #00, #0, #1	lbs.				
TORX ®: T6, T7, T8, T9, T10, T15						
Hex Inch: .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32"						
28522 ESD Safe Handle Range 15-80 Inch/oz.						