



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




RAD-CAB-EF142-3M

Order No.: 2884512

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2884512>

Antenna cable, 3 m in length; SMA (male) -> SMA (male), attenuation approx. 0.93 dB at 2.4 GHz; impedance 50 ohms

Commercial data

GTIN (EAN)	
sales group	L084
Pack	1 pcs.
Customs tariff	85442000
Catalog page information	Page 222 (AX-2009)

Product notes

WEEE/RoHS-compliant since:
03/22/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**Cable type**

Cable type	EF 142
Cable, attenuation	Approx. 0.93 dB/m

External sheath

Outer sheath, material	Radox (LSFH)
------------------------	--------------

External diameter	5 mm
Mechanical properties	
Bending radius, long-term	30 mm
Ambient temperature (operation)	-40 °C ... 105 °C
Ambient temperature (storage/transport)	-40 °C ... 105 °C
General data	
Impedance	50 Ω
Type of connection	SMA (male)

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;