



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



RAD-ISM Coaxial Antenna Cables

Data Sheet 2206B

June 2007

All of the accessories needed for installing a wireless system — antennas, adapters, cables, and surge suppression — are available from Phoenix Contact.

Please note that every connection between the radio and the antenna causes signal attenuation. The attenuation of a cable is proportional to the cable length; therefore use only as much cable as is absolutely necessary for the application.

Technical Data for the RAD-CAB-RG58-...

Connector Type	N(male) at both ends
Cable Type	RG-58U
Temperature Rating	-40°F to 167°F (-40°C to 75°C)
Outer Diameter	0.195 inches (11.43 mm)
Minimum Bending Radius	2 inches (50.8 mm)
Weight	2.5 pounds/100 feet
Insertion Attenuation	Approximately 13.7dB/100 feet
Jacket Material	PVC

Antenna Cable Length	Description	Order No.
10 feet	RAD-CAB-RG58-10	2867364
20 feet	RAD-CAB-RG58-20	2867212



Technical Data for the RAD-CAB-RG213-...

Connector Type	N(male) at both ends
Cable Type	RG-213U
Temperature Rating	-40°F to 176°F (-40°C to 80°C)
Outer Diameter	0.405 inches (10.29 mm)
Minimum Bending Radius	5 inches (127 mm)
Weight	10.4 pounds/100 feet
Insertion Attenuation	Approximately 7.6dB/100 feet
Jacket Material	Polyethylene

Antenna Cable Length	Description	Order No.
25 feet	RAD-CAB-RG213-25	2867597
40 feet	RAD-CAB-RG213-40	2867377
50 feet	RAD-CAB-RG213-50	2867225

Technical Data for the RAD-CAB-LMR240-...

Connector Type	N(male) at both ends
Cable Type	LMR-240
Temperature Rating	-40°F to 185°F (-40°C to 85°C)
Outer Diameter	0.24 inches (0.69 mm)
Minimum Bending Radius	0.75 inches (19.05 mm)
Weight	3.4 pounds/100 feet
Insertion Attenuation	Approximately 7.6dB/100 feet
Jacket Material	Polyethylene

Antenna Cable Length	Description	Order No.
10 feet	RAD-CAB-LMR240-10	5606124

Technical Data for the RAD-CAB-LMR400-...

Connector Type	N(male) at both ends
Cable Type	LMR-400
Temperature Rating	-40°F to 185°F (-40°C to 85°C)
Outer Diameter	0.405 inches (10.29 mm)
Minimum Bending Radius	1 inch (25.4 mm)
Weight	6.8 pounds/100 feet
Insertion Attenuation	Approximately 3.9dB/100 feet
Jacket Material	Polyethylene

Antenna Cable Length	Description	Order No.
20 feet	RAD-CAB-LMR400-20	5606125
60 feet	RAD-CAB-LMR400-60	2867380
80 feet	RAD-CAB-LMR400-80	2867393
100 feet	RAD-CAB-LMR400-100	2867238

Technical Data for the RAD-CAB-LMR500-...

Connector Type	N(male) at both ends
Cable Type	LMR-500
Temperature Rating	-40°F to 185°F (-40°C to 85°C)
Outer Diameter	0.50 inches (12.7 mm)
Minimum Bending Radius	1.25 inches (31.75 mm)
Weight	9.7 pounds/100 feet
Insertion Attenuation	Approximately 3.13dB/100 feet
Jacket Material	Polyethylene

Antenna Cable Length	Description	Order No.
25 feet	RAD-CAB-LMR500-25	5606126

Technical Data for the RAD-CAB-LMR600-...

Connector Type	N(male) at both ends
Cable Type	LMR-600
Temperature Rating	-40°F to 185°F (-40°C to 85°C)
Outer Diameter	0.59 inches (14.99 mm)
Minimum Bending Radius	1.5 inches (38.1 mm)
Weight	13.1 pounds/100 feet
Insertion Attenuation	Approximately 2.5dB/100 feet
Jacket Material	Polyethylene

Antenna Cable Length	Description	Order No.
125 feet	RAD-CAB-LMR600-125	2885171
150 feet	RAD-CAB-LMR600-150	2885184

Technical Data for the RAD-CAB-LMR900-...

Connector Type	N(male) at both ends
Cable Type	LMR-900
Temperature Rating	-40°F to 185°F (-40°C to 85°C)
Outer Diameter	0.87 inches (22.1 mm)
Minimum Bending Radius	3 inches (76.2 mm)
Weight	26.6 pounds/100 feet
Insertion Attenuation	Approximately 1.7dB/100 feet
Jacket Material	Polyethylene

Antenna Cable Length	Description	Order No.
200 feet	RAD-CAB-LMR900-200	2885197

The information given herein is based on data believed to be reliable, but Phoenix Contact makes no warranties expressed or implied as to its accuracy and assumes no liability arising out of its use by others. This publication is not to be taken as a license to operate under, or recommendation to infringe, any patent.

Canada
PHOENIX CONTACT Ltd.
 235 Watline Avenue
 Mississauga, Ontario L4Z 1P3
 Phone: 905-890-2820
 Technical Service: 800-890-2820
 Fax: 905-890-0180
 Website: www.phoenixcontact.ca

USA
PHOENIX CONTACT
 P.O. Box 4100
 Harrisburg, PA 17111-0100
 Phone: 800-888-7388
 717-944-1300
 Technical Service: 800-322-3225
 Fax: 717-944-1625
 E-mail: info@phoenixcon.com