

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

# RAD-ISM-900-ANT-OMNI-FG-6-N

Order No.: 2885579

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2885579>

Omnidirectional antenna, IP65 protection, gain 8 dBi, connection N (female)

## Commercial data

GTIN (EAN)	 4 046356 149471
Note	Made-to-order
sales group	H179
Pack	1 pcs.
Customs tariff	85177019
Catalog page information	Page 644 (IF-2009)

## Product notes

WEEE/RoHS-compliant since:  
07/01/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### General data

Frequency range	900 MHz
Horizontal beamwidth	360 °
Vertical beamwidth	15 °
Impedance	50 Ω
Gain	8 dBi

Type of connection	N (female)
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 80 °C
Width	6.05 cm
Height	180.34 cm

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;