



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




# RAD-PIG-EF316-SMA-SMA

Order No.: 2885618

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2885618>

Adapter cable, pigtail 50 cm SMA (male) -> SMA (male), insertion  
attenuation 1.5 dB at 2.4 GHz; impedance 50 ohms;

**Commercial data**

GTIN (EAN)	
sales group	H178
Pack	1 pcs.
Customs tariff	85442000
Catalog page information	Page 623 (IF-2009)

**Product notes**

WEEE/RoHS-compliant since:  
09/03/2007



[http://  
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)  
Please note that the data given  
here has been taken from the  
online catalog. For comprehensive  
information and data, please refer  
to the user documentation. The  
General Terms and Conditions of  
Use apply to Internet downloads.

**Technical data****General**

Connection 1	Plug connector connection
Type of connection	Type SMA (male)
Connection 2	Plug connector connection
Type of connection	Type SMA (male)
Fixed cable length	50 cm

Cable type	EF 316
Cable, attenuation	approx. 1.5 dB/m
Minimum bending radius	12.50 mm
External diameter	2.50 mm
Outer sheath, material	Radox (LSFH)
Connection name	Plug connector connection
Type of connection	Type SMA (male)
Ambient temperature (operation)	-40 °C ... 70 °C

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;