



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Patch panels - FL PF 2TX CAT 6 - 2891068

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Patch field with two RJ45 CAT6 network connections

Why buy this product

- Flexibility through the replacement of patch elements with fiber optic patch elements - Future proof through standardized installation according to CAT5 and CAT6
- Future proof through standardized installation according to CAT5 and CAT6
- Security through extension with FL PLUG GUARD



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 084383
GTIN	4046356084383

Technical data

Dimensions

Width	38 mm
Height	112 mm
Depth	88 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 55 °C (non-condensing)
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)

Interfaces

Interface 1	Ethernet (RJ45)
No. of ports	2

Patch panels - FL PF 2TX CAT 6 - 2891068

Technical data

Interfaces

Connection method	RJ45 CAT6
-------------------	-----------

Conformity with EMC directives

Developed in acc. with standard	ISO/IEC 11801, EN 50173, TIA/EIA 568B and IEC 60603-7
---------------------------------	---

General

Net weight	120.2 g
Housing material	Metal

Standards and Regulations

Developed in acc. with standard	ISO/IEC 11801, EN 50173, TIA/EIA 568B and IEC 60603-7
---------------------------------	---

Connection data

Conductor cross section	0.2 mm ² ... 0.32 mm ²
Connection cross section AWG	24 ... 22
Rated voltage (III/3)	50 V
Rated surge voltage	≥ 1 kV
Rated current	1 A

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>