

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China











42

Toll Free: (800) 494-6104

T-handle TorqueControl Tools





289 TorqueFix T-handle

EN ISO 6798, BS EN 26789, ASME B107.14M, +/- 6% Accuracy Ergonomic multi-component handle, light and compact.

With Certificate of calibration.

Item	Torque	Torque		•	
No.	In-lbs.	Nm	mm x mm	lbs.	pkg.
289 31	53.1	6	56 x 120	.81	1
289 33	70.8	8	56 x 120	.82	1
289 35	88.5	10	56 x 120	.79	1
289 37	106.2	12	56 x 120	.79	1
289 38	110.6	12.5	56 x 120	.80	1
289 39	123.9	14	56 x 120	.80	1

Each TorqueFix T-handle has unique serial number and certificate of calibration



289	TorqueFix	Adapter	For	1/4"	&	3/8"	Sockets	

Shaft CVM steel, hardened, corrosion protected.

Item		===	===		•	
No.	Size	mm	Inch	mm	lbs.	pkg.
289 26	1/4	100	3.9	6.0	.12	1
289 27	3/8	100	3.9	6.0	.15	1
	0, 0		0.0	0.0		·



See pages 211-215 for Sockets



289 25 TorqueFix Quick Release Bit Holder

Shaft CVM steel, hardened, corrosion protected.

Item		===	===		←	
No.	Size	mm	Inch	mm	lbs.	pkg.
289 25	1/4	125	4.9	6.0	.15	1



See pages 185-197 for Insert bits







289 TORX® Interchangeable Blades For TorqueFix T-Handle

TORX* tip blades on 6mm Hex shafts. High alloy chromevanadium-molybdenum steel, hardened, hard chromed.

Item	0		===		•		
No.	Size	mm	Inch	mm	lbs.	pkg.	
289 03	T15	130	5.1	4.0	.07	1	
289 04	T20	130	5.1	4.0	.07	1	
289 05	T25	130	5.1	4.0	.07	1	
289 06	T27	130	5.1	4.0	.07	1	
289 07	T30	130	5.1	4.0	.07	1	
289 08	T40	130	5.1	4.0	.07	1	







289 TORXPlus® Interchangeable Blades For TorqueFix T-Handle

TORXPlus® tip blades on 6mm Hex shafts. High alloy chrome-

vanadium-molybdenum steel, hardened, hard chromed.

Item	0	===			↓		
No.	Size	mm	Inch	mm	lbs.	pkg.	
289 10	IP15	130	5.1	4.0	.07	1	
289 11	IP20	130	5.1	4.0	.07	1	
289 12	IP25	130	5.1	4.0	.07	1	
289 13	IP27	130	5.1	4.0	.07	1	
289 14	IP30	130	5.1	4.0	.07	1	
289 15	IP40	130	5.1	4.0	.07	1	





289 Hex Metric Interchangeable Blades For TorqueFix T-Handle

Hex tip blades on 6mm Hex shafts. High alloy CVM steel,

hardened, satin hard chrome finish.

Haruene	u, saiii	maiu ci	IIIOIIIE	11111311.		
Item			===	↓		
No.	mm	mm	Inch	lbs.	pkg.	
289 16	3.0	130	5.1	.07	1	
289 17	4.0	130	5.1	.07	1	
289 18	5.0	130	5.1	.07	1	
289 19	6.0	130	5.1	.07	1	







289 Hex Inch Interchangeable Blades For TorqueFix T-Handle

Hex tip blades on 6mm Hex shafts. High alloy CVM steel, hardened, satin hard chrome finish.

Item		===	===	-			
No.	Inch	mm	Inch	lbs.	pkg.		
289 20	1/8	130	5.1	.07	1		
289 21	9/64	130	5.1	.07	1		
289 22	5/32	130	5.1	.07	1		
289 23	3/16	130	5.1	.07	1		
289 24	7/32	130	5.1	.07	1		

See T-handles On Pages 25-26, 30, 47-50



