



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Relay Module - UM-KS50/32MR/1/ADV551/SC/SO207 - 2900899

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



32-channel VARIOFACE relay module with screw connection and 50-pos. system connection. The power supply is designed redundantly, for Yokogawa ADV 551 card, module width: 232.5 mm

Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	1020.0 GRM
Custom tariff number	85369010
Country of origin	Germany

Technical data

Dimensions

Width	232.5 mm
Height	127.5 mm
Depth	44 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
---------------------------------	------------------

Input data

Nominal input voltage U_N	24 V DC
Input voltage range in reference to U_N	0.8 ... 1.1
Typical input current at U_N	9 mA (per relay)
Protective circuit/component	Damping diode
Status display/channel	Yellow LED

Output data

Contact type	Single contact, 1 N/O contact
Contact material	Ag alloy, hard gold-plated
Maximum switching voltage	230 V AC
Limiting continuous current	max. (2 x 8 A)

Relay Module - UM-KS50/32MR/1/ADV551/SC/SO207 - 2900899

Technical data

General

Mounting position	any
Designation	Air and creepage distances, input
Standards/regulations	EN 50178
Rated insulation voltage	63 V
Rated surge voltage	0.6 kV (basic insulation)
Pollution degree	2
Surge voltage category	II
Designation	Air and creepage distances, output
Standards/regulations	EN 50178
Rated insulation voltage	260 V
Rated surge voltage	4 kV (basic insulation)
Pollution degree	2
Surge voltage category	III
Designation	Air and creepage distances, input/output
Standards/regulations	EN 50178
Rated insulation voltage	260 V
Rated surge voltage	6 kV (Reinforced insulation)
Pollution degree	2
Surge voltage category	III

Connection data for connection 1

Connection name	Supply
Connection method	Screw connection
Number of positions	8
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

Classifications

eCl@ss

eCl@ss 4.0	27371102
eCl@ss 4.1	27371102
eCl@ss 5.0	27371001
eCl@ss 5.1	27371001

Relay Module - UM-KS50/32MR/1/ADV551/SC/SO207 - 2900899

Classifications

eCl@ss

eCl@ss 6.0	27371001
eCl@ss 7.0	27371001
eCl@ss 8.0	27371001

ETIM

ETIM 2.0	EC001437
ETIM 3.0	EC001437
ETIM 4.0	EC001423
ETIM 5.0	EC001437

UNSPSC

UNSPSC 6.01	30211916
UNSPSC 7.0901	39121515
UNSPSC 11	39121515
UNSPSC 12.01	39121515
UNSPSC 13.2	39121515

Approvals

Approvals

Approvals

CSA

Ex Approvals

Approvals submitted

Approval details

CSA
