



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Front adapters - FLK 50-PA/EZ-DR/KS/ 100/YUC - 2900991

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cast front adapter with attached round cable and a 50-pos. socket strip injection-molded on both sides for the connection of Yokogawa controllers. Cable length: 1.0 m

Illustration shows the product FLK 50-PA/EZ-DR/KS/ 200/YUC

RoHS

Key Commercial Data

| | |
|--------------------------------------|-----------|
| Packing unit | 1 STK |
| Weight per Piece (excluding packing) | 340.000 g |
| Custom tariff number | 85444290 |
| Country of origin | Germany |

Technical data

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -20 °C ... 70 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

General

| | |
|--------------------------|---------------------------|
| Nominal voltage U_N | 30 V DC |
| Max. permissible current | 500 mA (per path at 70°C) |

Connection data 1

| | |
|-----------------------|--------------------------------|
| Connection name | Control side |
| Connection method | Yokogawa, I/O cards compatible |
| Torque | 0.5 Nm (Screw connection) |
| Number of connections | 1 |
| Number of positions | 50 |

Connection data 2

Front adapters - FLK 50-PA/EZ-DR/KS/ 100/YUC - 2900991

Technical data

Connection data 2

| | |
|-----------------------|---------------------------|
| Connection name | Field level |
| Connection method | Yokogawa, KS compatible |
| Torque | 0.5 Nm (Screw connection) |
| Number of connections | 1 |
| Number of positions | 50 |

Cable

| | |
|-----------------------------|------------------------------------|
| Structural data | in acc. to UL style 2464/1061 |
| Individual wires per module | 7 |
| Single wire, material | Cu tin-plated |
| Single wire, cross section | 0.14 mm ² |
| External diameter | 11 mm |
| Length of cable | 1 m |
| Outer sheath, material | PVC |
| External sheath, color | gray RAL 7035 |
| Shielding | yes |
| Halogen-free cable | No |
| Max. conductor resistance | 0.16 Ω/m |
| Cable insulation resistance | approx. 153 MΩ/km |
| Cable impedance | approx. 120 Ω |
| Cable resistance | approx. 155 Ω/km |
| Cable capacity | approx. 130 pF/m |
| Insulation | Semi-rigid PVC |
| Flame resistance | IEC 60332-3-22 |
| Resistance to oil | DIN VDE 0472 Part 803, test type B |

Supported controller

| | |
|---------------------|--------------------------|
| Controller | YOKOGAWA CS3000 CentumVP |
| - suitable I/O card | ADV151 |
| | ADV551 |
| Controller | YOKOGAWA STARDOM |
| - suitable I/O card | NFDV151 |
| | NFDV551 |

Standards and Regulations

| | |
|-------------------|------------------------------------|
| Resistance to oil | DIN VDE 0472 Part 803, test type B |
| Flame resistance | IEC 60332-3-22 |

Drawings

Front adapters - FLK 50-PA/EZ-DR/KS/ 100/YUC - 2900991

Connection diagram

| 50-pos. connector to the I/O card | 50-pos. connector to the module | Wire color |
|---|---------------------------------------|---------------|
| 1 | 50 | black |
| 2 | 49 | brown |
| 3 | 48 | red |
| 4 | 47 | orange |
| 5 | 46 | yellow |
| 6 | 45 | green |
| 7 | 44 | blue |
| 8 | 43 | violet |
| 9 | 42 | gray |
| 10 | 41 | white |
| 11 | 40 | white-black |
| 12 | 39 | white-brown |
| 13 | 38 | white-red |
| 14 | 37 | white-orange |
| 15 | 36 | white-yellow |
| 16 | 35 | white-green |
| 17 | 34 | white-blue |
| 18 | 33 | white-violet |
| 19 | 32 | white-gray |
| 20 | 31 | brown-black |
| 21 | 30 | brown-red |
| 22 | 29 | brown-orange |
| 23 | 28 | brown-yellow |
| 24 | 27 | brown-green |
| 25 | 26 | brown-blue |
| 26 | 25 | brown-violet |
| 27 | 24 | brown-gray |
| 28 | 23 | brown-white |
| 29 | 22 | green-black |
| 30 | 21 | green-brown |
| 31 | 20 | green-red |
| 32 | 19 | green-orange |
| 33 | 18 | green-blue |
| 34 | 17 | green-violet |
| 35 | 16 | green-gray |
| 36 | 15 | green-white |
| 37 | 14 | yellow-black |
| 38 | 13 | yellow-brown |
| 39 | 12 | yellow-red |
| 40 | 11 | yellow-orange |
| 41 | 10 | yellow-blue |
| 42 | 9 | yellow-violet |
| 43 | 8 | yellow-gray |
| 44 | 7 | yellow-white |
| 45 | 6 | gray-black |
| 46 | 5 | gray-brown |
| 47 | 4 | gray-red |
| 48 | 3 | gray-orange |
| 49 | 2 | gray-yellow |
| 50 | 1 | gray-green |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27250313 |
| eCl@ss 4.1 | 27250313 |
| eCl@ss 5.0 | 19030502 |
| eCl@ss 5.1 | 19030502 |
| eCl@ss 6.0 | 27249205 |
| eCl@ss 7.0 | 27249205 |
| eCl@ss 8.0 | 27249290 |

Front adapters - FLK 50-PA/EZ-DR/KS/ 100/YUC - 2900991

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 9.0 | 27242292 |
|------------|----------|

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000237 |
| ETIM 4.0 | EC000237 |
| ETIM 5.0 | EC002584 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 26121620 |
| UNSPSC 7.0901 | 26121620 |
| UNSPSC 11 | 26121620 |
| UNSPSC 12.01 | 26121620 |
| UNSPSC 13.2 | 26121620 |

Approvals

Approvals


Approvals


EAC / UL Listed / cUL Listed / cULus Listed

Ex Approvals

Approval details

| |
|-------------------------|
| EAC RU C-DE.A*30.B00767 |
|-------------------------|

| |
|---|
| <ul style="list-style-type: none"> UL Listed  http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 238705 |
|---|

| |
|--|
| <ul style="list-style-type: none"> cUL Listed  http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 238705 |
|--|

Front adapters - FLK 50-PA/EZ-DR/KS/ 100/YUC - 2900991

Approvals

