

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









# Jumper - BRIDGE- 7-3M - 2901698

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



3-phase loop bridge for 7 CONTACTRON modules, with screw connection and 22.5 mm housing width, connecting cable: 3 m, with ferrules included.

### Why buy this product

- ☐ Only suitable for CONTACTRON series with screw connection ELR H3...-SC-..., ELR H5...-SC-..., ELR (W)3..., EMM...IFS
- ☐ Bridging of 2 to 10 devices with maximum module spacing of 22.5 mm
- ☑ Up to 575 V AC/3 x 25 A



# **Key Commercial Data**

Packing unit	1 STK
GTIN	4 046356 624633
GTIN	4046356624633

## Technical data

### Dimensions

Length of the connecting cable	3 m
Width	22.5 mm

#### General

Operating voltage range	42 V AC 575 V AC
Operating current	≤ 25 A
Number of bridgeable modules	7
Connecting cable length	3 m
Color	green
Conductor cross section	2.5 mm²

### **Environmental Product Compliance**

China RoHS	Environmentally Friendly Use Period = 50




# Jumper - BRIDGE- 7-3M - 2901698

# Technical data

**Environmental Product Compliance** 

For details about hazardous substances go to tab "Downloads",
Category "Manufacturer's declaration"

# Drawings






Figure shows the version BRIDGE- 4	
Approvals	
Approvals	
Approvals	
EAC	
Ex Approvals	
Approval details	
EAC	RU C- DE.A*30.B.01742



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300

Fax +49 5235 3 41200

http://www.phoenixcontact.com