



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Antenna cable - RAD-PIG-RSMA/N-0.5 - 2903263

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Antenna cable, 0.5 m in length; N (male) -> RSMA (male), impedance 50 ohms



The illustration shows a version of the product

Product Description

Coaxial antenna adapter cable, N (male) to RSMA (male), 50 Ω, 0.5 m

Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	50.0 g
Custom tariff number	85442000
Country of origin	United States

Technical data

Dimensions

Fixed cable length	0.5 m
External diameter	4.95 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
---------------------------------	------------------

General

Connection method	RSMA (male)
	N (male)
Cable type	195
Minimum bending radius	12.70 mm
Frequency range	900 MHz
	2.4 GHz
	5 GHz
Impedance	50 Ω

Attenuation

Antenna cable - RAD-PIG-RSMA/N-0.5 - 2903263

Technical data

Attenuation

868 / 900 MHz	0.37 dB
2.4 GHz	0.5 dB
5 GHz	0.65 dB

Classifications

eCl@ss

eCl@ss 4.0	27230207
eCl@ss 4.1	27250312
eCl@ss 5.0	27242208
eCl@ss 5.1	27061802
eCl@ss 6.0	27242208
eCl@ss 7.0	27242208
eCl@ss 8.0	27060310

ETIM

ETIM 3.0	EC001423
ETIM 4.0	EC000019
ETIM 5.0	EC001682

UNSPSC

UNSPSC 6.01	30211506
UNSPSC 7.0901	43223108
UNSPSC 11	39121008
UNSPSC 12.01	43223108
UNSPSC 13.2	43223108